



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

| Size in Sq.mm. | 1 Core | 2 Core | 3 Core | 3.5 Core | 4 Core |
|----------------|-----------------|---------------|---------------|----------|---------------|
| | A2XWaY / A2XFaY | A2XWY / A2XFY | A2XWY / A2XFY | A2XFY | A2XWY / A2XFY |
| 2.5 | | 139 | 148 | | 172 |
| 4 | | 152 | 172 | | 202 |
| 6 | | 199 | 215 | | 258 |
| 10 | | 251 | 274 | | 311 |
| 16 | 156 | 255 | 284 | | 372 |
| 25 | 203 | 298 | 364 | 429 | 456 |
| 35 | 242 | 349 | 479 | 530 | 600 |
| 50 | 292 | 444 | 620 | 710 | 778 |
| 70 | 374 | 622 | 829 | 960 | 1058 |
| 95 | 416 | 747 | 1035 | 1200 | 1340 |
| 120 | 502 | 910 | 1292 | 1473 | 1660 |
| 150 | 591 | 1142 | 1530 | 1730 | 1980 |
| 185 | 724 | 1363 | 1920 | 2189 | 2427 |
| 240 | 919 | 1744 | 2455 | 2810 | 3220 |
| 300 | 1130 | 2125 | 3040 | 3434 | 4060 |
| 400 | 1426 | 2615 | 3940 | 4390 | 5160 |
| 500 | 1742 | 3701 | 5224 | 6055 | 7004 |
| 630 | 2145 | 4659 | 6820 | 8061 | 9264 |
| 800 | 2672 | | | | |
| 1000 | 3376 | | | | |

EXTRA FOR SPECIAL CONSTRUCTION:

| | |
|-------------------------------------|------|
| a) Round Wire Armouring | |
| - 2 x 16 & above | 30% |
| - 3 x 16 & 3.5CX25 & above | 30% |
| - 4 x 10 & above | 30% |
| - For Single core 95 & above | 30% |
| b) Stranding 10 sq.mm and below | 10% |
| c) Extruded PVC Innersheath Up 50 | 7.5% |
| Extruded PVC Innersheath 70 & Above | 4% |
| d) HR PVC Insulation | 15% |
| e) HR PVC Inner Sheath | 7.5% |
| f) HR PVC Outer Sheath | 7.5% |
| g) Oxygen Index (FR) | 4% |
| h) PVC Insulated Cables | 12% |

| Cable Size (Sq.mm) | FRLS Loading Factor | | LSZH | |
|--------------------|---------------------|-------------------------|--------------|--------------|
| | Inner Sheath | Outer Sheath | Inner Sheath | Outer Sheath |
| | | Armoured | | |
| | | Power (Al.) | | |
| Upto 16 | 15% | 11.5% | 22.5% | 30% |
| 25 - 50 | 11.5% | 11.5% | 18% | 22.5% |
| 70 & above | 7.5% | 7.5% | 22.5% | 18% |
| | | Power Single Core (Al.) | | |
| Upto 16 | -N.A- | 15% | -N.A- | 37.5% |
| 25 - 50 | -N.A- | 15% | -N.A- | 30% |
| 70 & above | -N.A- | 11.5% | -N.A- | 26% |

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

| Size in Sq.mm. | 1 Core | 2 Core | 3 Core | 3.5 Core | 4 Core |
|----------------|--------|--------|--------|----------|--------|
| | A2XY | A2XY | A2XY | A2XY | A2XY |
| 4 | | 88 | 110 | | 132 |
| 6 | | 122 | 146 | | 178 |
| 10 | | 178 | 199 | | 234 |
| 16 | 85 | 181 | 224 | | 297 |
| 25 | 133 | 234 | 316 | 401 | 421 |
| 35 | 164 | 307 | 435 | 471 | 522 |
| 50 | 210 | 384 | 536 | 639 | 699 |
| 70 | 279 | 554 | 771 | 872 | 1004 |
| 95 | 366 | 644 | 938 | 1109 | 1196 |
| 120 | 438 | 802 | 1225 | 1426 | 1451 |
| 150 | 527 | 998 | 1413 | 1669 | 1798 |
| 185 | 647 | 1190 | 1781 | 2134 | 2224 |
| 240 | 764 | 1557 | 2299 | 2561 | 2964 |
| 300 | 952 | 1902 | 2817 | 3319 | 3610 |
| 400 | 1194 | 2375 | 3515 | 4148 | 4753 |
| 500 | 1563 | 3089 | 4979 | 5837 | 6629 |
| 630 | 1963 | 3934 | 6558 | 7743 | 8872 |
| 800 | 2494 | | | | |
| 1000 | 3209 | | | | |

EXTRA FOR SPECIAL CONSTRUCTION:

| | |
|-------------------------------------|------|
| a) Stranding 10 sq.mm and below | 10% |
| b) Extruded PVC Innersheath Up 50 | 7.5% |
| Extruded PVC Innersheath 70 & Above | 4% |
| c) HR PVC Insulation | 15% |
| d) HR PVC Inner Sheath | 7.5% |
| e) HR PVC Outer Sheath | 7.5% |
| f) Oxygen Index (FR) | 4% |
| g) PVC Insulated Cables | 12% |

| Cable Size (Sq.mm) | FRLS Loading Factor | | LSZH | |
|--------------------|-------------------------|--------------|--------------|--------------|
| | Inner Sheath | Outer Sheath | Inner Sheath | Outer Sheath |
| | | Unarmd. | | |
| | Power (Al.) | | | |
| Upto 16 | 15% | 11.5% | 22.5% | 30% |
| 25 - 50 | 11.5% | 11.5% | 18% | 22.5% |
| 70 & above | 7.5% | 7.5% | 22.5% | 18% |
| | Power Single Core (Al.) | | | |
| Upto 16 | -N.A.- | 15% | -N.A.- | 37.5% |
| 25 - 50 | -N.A.- | 15% | -N.A.- | 30% |
| 70 & above | -N.A.- | 12% | -N.A.- | 26% |

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

| Cable Size in sq.mm | 1 Core | 2 Core | 3 Core | 4 Core | 5 Core | 6 Core | 7 Core |
|---------------------|---------------|-------------|-------------|--------|-------------|-------------|-------------|
| | 2XWaY / 2XFaY | 2XWY / 2XFY | 2XWY / 2XFY | 2XFY | 2XWY / 2XFY | 2XWY / 2XFY | 2XWY / 2XFY |
| 4 | | 330 | 442 | 557 | 788 | 971 | 1097 |
| 6 | | 451 | 611 | 788 | 1085 | 1308 | 1509 |
| 10 | | 718 | 982 | 1290 | 1814 | | |
| 16 | 611 | 1000 | 1468 | 1890 | 2701 | | |

Control Cables (Rate in Rs. Per Mtr.)

| Number of Cores | 2XWY/2XFY | | Number of Cores | 2XWY/2XFY | |
|-----------------|------------|------------|-----------------|------------|------------|
| | 1.5 Sq.mm. | 2.5 Sq.mm. | | 1.5 Sq.mm. | 2.5 Sq.mm. |
| 2 | 177 | 243 | 14 | 758 | 1184 |
| 3 | 215 | 315 | 16 | 850 | 1344 |
| 4 | 265 | 395 | 19 | 1009 | 1611 |
| 5 | 317 | 469 | 24 | 1263 | 2018 |
| 6 | 373 | 556 | 27 | 1392 | 2508 |
| 7 | 416 | 631 | 30 | 1549 | 2914 |
| 8 | 536 | 727 | 37 | 2094 | 3390 |
| 10 | 606 | 912 | 44 | 2603 | 4084 |
| 12 | 665 | 1047 | 61 | 3799 | 5815 |

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

| | |
|--|-----------|
| A) Tinning | 3% |
| B) Stranding (Upto 6 SQ.MM) | 4% |
| C) Extruded Innersheath | 4% |
| D) Round Wire Armouring | |
| 1C x 95 sq. mm & above | 9% |
| 1.5 sq.mm - 12 core & above | 18% |
| 2.5 sq.mm - 9 core & above | 18% |
| 10 sq.mm - 4 core & above | 18% |
| 16 sq.mm - 2 core & above | 18% |
| 16 sq.mm - 3 core & above | 18% |
| E) OXYGEN INDEX (FR) | 4% |
| F) HR PVC Insulatoin | 10% |
| HR I/S & O/S | 7.5% Each |
| G) FRLS Loading-Power Cable (upto 6 Sq.mm.) | 11.50% |
| FRLS Loading-Power Cable (10 Sq.mm. & above) | 6% |
| H) PVC Insulated Cables | 7.5% |

| FRLS Loading Factor- Control Cable | | | LSZH | |
|------------------------------------|--------------|--------------|--------------|--------------|
| Cores | Inner Sheath | Outer Sheath | Inner Sheath | Outer Sheath |
| | | Armoured | | |
| 2 to 4 Core | 7.5% | 9% | 22.5% | 22.5% |
| 5 to 10 Core | 7.5% | 6% | 22.5% | 22.5% |
| 12 & Above | 7.5% | 6% | 18% | 18% |

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

| Cable Size in sq.mm | 1 Core | 2 Core | 3 Core | 4 Core |
|---------------------|--------|--------|--------|--------|
| | 2XY | 2XY | 2XY | 2XY |
| 4 | | 280 | 399 | 486 |
| 6 | | 398 | 566 | 688 |
| 10 | | 691 | 950 | 1136 |
| 16 | 511 | 916 | 1407 | 1764 |

Control Cables (Rate in Rs. Per Mtr.)

| Number of Cores | 2XY | | Number of Cores | 2XY | |
|-----------------|------------|------------|-----------------|------------|------------|
| | 1.5 Sq.mm. | 2.5 Sq.mm. | | 1.5 Sq.mm. | 2.5 Sq.mm. |
| 2 | 131 | 188 | 14 | 627 | 1126 |
| 3 | 164 | 264 | 16 | 754 | 1290 |
| 4 | 212 | 345 | 19 | 903 | 1554 |
| 5 | 260 | 421 | 24 | 1143 | 1963 |
| 6 | 307 | 477 | 27 | 1253 | 2415 |
| 7 | 354 | 573 | 30 | 1483 | 2703 |
| 8 | 472 | 662 | 37 | 1987 | 3174 |
| 10 | 549 | 827 | 44 | 2400 | 3716 |
| 12 | 567 | 1000 | 61 | 3617 | 5290 |

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

| | |
|--|-----------|
| A) Tinning | 3% |
| B) Stranding (Upto 6 SQ.MM) | 4% |
| C) Extruded Innersheath | 4% |
| D OXYGEN INDEX (FR) | 4% |
| E) HR PVC Insulation | 10% |
| HR PVC I/S & O/S | 7.5% Each |
| F) FRLS Loading-Power Cable (upto 6 Sq.mm.) | 11.50% |
| FRLS Loading-Power Cable (10 Sq.mm. & above) | 6% |
| G) PVC Insulated Cables | 7.5% |

| FRLS Loading Factor- Control Cable | | | LSZH | |
|------------------------------------|--------------|--------------|--------------|--------------|
| Cores | Inner Sheath | Outer Sheath | Inner Sheath | Outer Sheath |
| | Unarmd | | | |
| 2 - 4 | 7.5% | 9% | 22.5% | 22.5% |
| 5 - 10 | 7.5% | 6% | 22.5% | 22.5% |
| 12 & Above | 7.5% | 6% | 18% | 18% |

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

| Cable Size in sq.mm | 1 Core | 2 Core | 3 Core | 3.5 Core | 4 Core | 5 Core |
|---------------------|---------------|-------------|-------------|----------|-------------|-------------|
| | 2XWaY / 2XFaY | 2XWY / 2XFY | 2XWY / 2XFY | 2XFY | 2XWY / 2XFY | 2XWY / 2XFY |
| 25 | 924 | 1568 | 2235 | 2688 | 2945 | 4218 |
| 35 | 1244 | 2193 | 3096 | 3512 | 4072 | 5865 |
| 50 | 1749 | 2969 | 4265 | 4939 | 5622 | 7824 |
| 70 | 2418 | 4104 | 6019 | 7075 | 8361 | |
| 95 | 3329 | 5988 | 8897 | 10150 | 11635 | |
| 120 | 4130 | 7139 | 10964 | 13400 | 14800 | |
| 150 | 5062 | 8939 | 13601 | 15456 | 17875 | |
| 185 | 6190 | 11065 | 17069 | 19932 | 22673 | |
| 240 | 7892 | 14256 | 22176 | 25644 | 29219 | |
| 300 | 9968 | 18055 | 27512 | 32256 | 37178 | |
| 400 | 13373 | 24562 | 36288 | 41530 | 47578 | |
| 500 | 16538 | | | | | |
| 630 | 20793 | | | | | |
| 800 | 26317 | | | | | |
| 1000 | 33081 | | | | | |

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

| Cable Size in sq.mm | 1 Core | 2 Core | 3 Core | 3.5 Core | 4 Core | |
|---------------------|--------|--------|--------|----------|--------|--|
| | 2XY | 2XY | 2XY | 2XY | 2XY | |
| 25 | 807 | 1518 | 2114 | 2360 | 2766 | |
| 35 | 1093 | 2085 | 2895 | 3312 | 3864 | |
| 50 | 1565 | 2858 | 4012 | 4730 | 5255 | |
| 70 | 2178 | 3793 | 5713 | 6805 | 7999 | |
| 95 | 3177 | 5650 | 8713 | 10102 | 11239 | |
| 120 | 3977 | 6912 | 10251 | 13186 | 14150 | |
| 150 | 4891 | 8651 | 13019 | 14910 | 17506 | |
| 185 | 6060 | 10670 | 16081 | 18838 | 22220 | |
| 240 | 7805 | 13662 | 21327 | 24778 | 28634 | |
| 300 | 9817 | 17023 | 26035 | 30651 | 35385 | |
| 400 | 12906 | 22722 | 33327 | 38176 | 44562 | |
| 500 | 16429 | | | | | |
| 630 | 20683 | | | | | |
| 800 | 26196 | | | | | |
| 1000 | 32751 | | | | | |

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

| | |
|---|-----------|
| A) Tinning | 3% |
| B) Stranding (Upto 6 SQ.MM) | 4% |
| C) Extruded Innersheath | 4% |
| D) Round Wire Armouring | |
| 1C x 95 sq. mm & above | 9% |
| 10 sq.mm - 4 core & above | 18% |
| 16 sq.mm - 2 core & above | 18% |
| 16 sq.mm - 3 core & above | 18% |
| E) OXYGEN INDEX (FR) | 4% |
| F) HR PVC Insulatoin | 10% |
| HR I/S & O/S | 7.5% Each |
| G) FRLS Loading-Power Cable (10 Sq.mm. & above) | 6% |
| H) PVC Insulated Cables | 7.5% |

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

| | (Rate in Rs. Per Mtr.) | | | | | |
|----------------|--------------------------|-------------------------|------------|-----------|-----------|------------|
| Size in Sq.mm. | 3.3 KV (UE) / 6.6 KV (E) | 6.6 KV (UE) / 11 KV (E) | 11 KV (UE) | 22 KV (E) | 33 KV (E) | 33 KV (UE) |
| 35 | | 1248 | | | | |
| 50 | | 1467 | | | | |
| 70 | 1649 | 1757 | | | | |
| 95 | 1860 | 2032 | 2560 | 2817 | 3680 | |
| 120 | 2252 | 2410 | 3031 | 3127 | 4036 | |
| 150 | 2644 | 2788 | 3347 | 3572 | 4511 | 5147 |
| 185 | 3032 | 3217 | 3837 | 3989 | 4933 | 5648 |
| 240 | 3697 | 3882 | 4651 | 4820 | 5729 | 6252 |
| 300 | 4420 | 4594 | 5306 | 5461 | 6340 | 7146 |
| 400 | 5606 | 5733 | 6203 | 6470 | 7598 | 8505 |

EXTRA FOR SPECIAL CONSTRUCTION:

| | |
|---|-------|
| 1) Extruded PVC Inner Sheath | 4.5% |
| 2) Pressure Extruded PVC Innersheath | 19.5% |
| 3) Round Wire Armouring - Up to 11 KV (E) | 30% |
| 11 KV (UE) & Above | 33% |
| 4) FRLS PVC Inner Sheath | 7.5% |
| 5) FRLS PVC Outer Sheath | 7.5% |
| 6) FR Sheath with Oxygen Index | 4.5% |

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 04/2022-23 Dtd : 1st February 2023

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

| Size in Sq.mm. | 3.3 KV (UE) / 6.6 KV (E) | | 6.6 KV (UE) / 11 KV (E) | | 11 KV (UE) | | 22 KV (E) | | 33 KV (E) | | 33 KV (UE) | |
|----------------|--------------------------|--------------------|-------------------------|--------------------|-------------------------|--------------------|-------------------------|--------------------|-------------------------|--------------------|-------------------------|--------------------|
| | Al. Flat Strip Armoured | Al. Round Armoured | Al. Flat Strip Armoured | Al. Round Armoured | Al. Flat Strip Armoured | Al. Round Armoured | Al. Flat Strip Armoured | Al. Round Armoured | Al. Flat Strip Armoured | Al. Round Armoured | Al. Flat Strip Armoured | Al. Round Armoured |
| 240 | 1307 | 1371 | 1437 | 1508 | 1626 | 1712 | 1664 | 1753 | 2141 | 2256 | 2452 | 2583 |
| 300 | 1497 | 1580 | 1648 | 1739 | 1853 | 1951 | 1896 | 1996 | 2531 | 2668 | 2725 | 2871 |
| 400 | 1820 | 1919 | 1976 | 2079 | 2200 | 2314 | 2249 | 2365 | 2904 | 3051 | 3074 | 3233 |
| 500 | 2323 | 2448 | 2409 | 2531 | 2764 | 2906 | 2764 | 2906 | 3422 | 3604 | 3566 | 3759 |
| 630 | 2807 | 2957 | 2883 | 3033 | 3266 | 3433 | 3266 | 3433 | 3979 | 4187 | 4143 | 4359 |
| 800 | 3489 | 3668 | 3537 | 3825 | 3912 | 4118 | 3912 | 4118 | 4710 | 4955 | 4915 | 5168 |
| 1000 | 4127 | 4344 | 4532 | 4774 | 4849 | 5099 | 4849 | 5099 | 5763 | 6042 | 6195 | 6519 |

EXTRA FOR SPECIAL CONSTRUCTION:

| | |
|--------------------------|-------|
| 1) FRLS PVC Inner Sheath | 11.5% |
| 2) FRLS PVC Outer Sheath | 7.5% |
| 3) Oxygen Index | 4.5% |

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.