

Price list

Bussmann Fusegear Solutions

Effective From 1st March, 2022

Leader in Circuit Protection Solutions



Bussmann
by **EAT•N**

EatonElectricalIndia@eaton.com

About **EAT•N**

Eaton is a global leading power management company headquartered in USA, serving customers across the world. Our proven technologies enable customers to generate more power using fewer resources, answering the demands of today's fast changing world. Eaton products and services provide the power inside thousands of products and projects – from energy efficient buildings, cities, infrastructure to next generation aircraft, cars, trucks and machines. Eaton is a Fortune 500 company recognized amongst the most admired firms in our industry.

Eaton Power Quality Private Limited, India, is a 100% subsidiary and a part of electrical sector of Eaton Corporation. We are catering to every industrial segment with versatile solutions which includes Switchgear: LV & MV Solutions, Fusegear: LV & MV solutions, UPSs and software solutions.

Operating in
175
countries

92,000+
employees

100+
years of
experience

\$ 19.6
BN. 2021 IN
SALES

18,000+
patents

The Fusion Of Our Heritage

Meeting power management needs around the world



Toll free number: 1800 425 5758, 1800 102 4620 Emergency number : 893 922 2522

✉ helpdeskelectrical@eaton.com

Eaton's Product Range

Low Voltage Distribution Products

Air Circuit Breakers	PSL / IZMX
Molded Case Circuit Breakers	PDC / NZM / BZM
Disconnectors	P / PN
Mining Duty Breakers	
ATS	



Contactors

Mini Contactors & Control Relays	DILEM / DILEEM / DILER
Control Relays & Power Contactors	DILM / DILA
Vacuum Contactors	DILM / DILH /V201
4 Pole Contactors	DILMP
Capacitor Duty Contactors	DILK
Lighting Duty Contactors	DILL
DC Mill Duty Contactors	
DC Power Contactors	
Definite Purpose Contactors	



Overload Relays

Thermal Magnetic Overload Relay	ZB/ZE/ZEB
Electronic Overload Relay	Motor Insight, C440
Thermistor Based Overload Relays	EMT6



Motor Protection Circuit Breakers (MPCB)

MPCB with Push Button Control	PKZM01
MPCB with Rotary Handle Control	PKZM0
MPCB with Electronic Release	PKE



Low Voltage Control Products

Pilot Devices (22.5mm & 16mm)	RMQTitan (M22) / A22
Pilot Devices (30.5mm)	E30/E34/10250T
Foot & Palm Switch	FAK
Signal Towers	SL
Pressure Switches	MCS
Position Switches / Safety Switches	LS
Sensors	Inductive / Capacitive / Optical
Limit Switches	Precision / Mini / Metal / Metal-IP67 / Hazardous Applications



Effective 1st March, 2022

Price list

Eaton's Product Range

Cam Switches & Switch - Disconnectors

Cam Switches upto 132KW.....	T
Switch-Disconnecter upto 110KW/315A	P
ATEX Rated Enclosures	T/P



Electronic Relays

Safety Relay	ESR5
Safety Control Relays	Easy Safety
Timing Relays	ETR2 / ETR4
Measuring & Monitoring Relays	EMR



Automation Products

Relays	Easy500/700/800
PLC's	XC / EC4
HMI/ HMI-PLC's	XVC
Smartwire Darwin Communication System	



Motor Starters

DOL / RDOL Starter upto 32A with PKZM0	
DOL / RDOL Starter upto 32A with PKE	
Soft Starters upto 900KW.....	S8014/S8114
Variable Speed Starter	DE1
Variable Speed Drive	DG1



Enclosures

IP65, Outdoor rated Polycarbonate Opaque/Transparent	CI /CI-K
MCB Individual Enclosure	AE..
MCCB / Switch Disconnecter	MCCB...
Fuse Enclosure	RS..



Solar Products

Disconnectors upto 60A, 1000V DC rated	
Disconnectors, 160A - 1400A, 1500V DC rated	
Fuse & Fuse Base, 1000V DC	
Inverters upto 1MW	
DC Combiner Boxes	
AC Switchgear	



Contents

Low Voltage Fuse Links & Fuse Holders	
HRC Fuse Fittings & Bases	6
Low Voltage BS88 Type of Fuse Links	6 - 9
Low Voltage NH Type of Fuse Links	10
Highspeed Voltage Fuse Links	
BS 88 Semi-Conductor Protection, Highspeed Fuses	11 - 12
Accessories for BS 88 Highspeed Fuses	13
Medium Voltage Fuse Links	
BS Type HV Fuses for use in Air	14 - 15
HV Fuses for use in Oil	16
HV Fuses for use in PT/VT & Auxillary Transformer	16
HV Fuses for use in for HV Motor Circuits	17
Fuse Range	
Low Voltage BS88 Type of Fuse Links Range	18 - 21
Highspeed Voltage Fuse Links Range	22
Medium Voltage Fuse Links	23
Cross Reference Chart	
Cross Reference Chart	24

HRC Fuse Fittings & Fuse Bases

Fuse Base for LV NH Type of Fuse

IS / BS Size Reference	Description	No. of Poles	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
00 / C00	Fuse Base	Single	160NHG00B/ 100NHG000B	160	SB00-PB	690	400	3	3	O
00 / C00	Top Cover	Single	160NHG00B/ 100NHG000B	160	TC00	690	60	3	3	O
00 / C00	Terminal Shield	Single	160NHG00B/ 100NHG000B	160	IPB00	690	60	6	6	O
00 / C00	Terminal Shield	Single	160NHG00B/ 100NHG000B	160	TS00	690	50	6	6	O




Fuse Fittings for LV BS Type of Fuses

IS / BS Size Reference	Tag Type	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1	Clip on	Front (#)	F06/NSD	20	FA20	500	160	10	10	N
		Front	F06/NSD	32	FA32	500	170	10	10	N
		Back	F06/NSD	32	FB32	500	235	10	10	N
		Busbar	F06/NSD	32	FD32	500	245	10	10	N
A2	Offset Bolted	Front	H07/F07/AAO	32	HA32	500	300	5	5	N
		Busbar	H07/F07/AAO	32	HD32	500	350	5	5	N
A3	Offset Bolted	Front	TO7/BAO/KO7	63	KA63	500	365	5	5	N
		Busbar	TO7/BAO/KO7	63	KD63	500	440	5	5	N
A4	Offset Bolted	Front	L14/KL14/M14	100/125	LA125	500	1050	1	1	N
		Busbar	L14/KL14/M14	100/125	LD125	500	1365	1	1	N
F1	Clip on	Front	F06/NSD	32	32NNSF	550	200	10	10	N
		Front	ESD	63	63ENSF	415	1715	5	5	O

Safe lock Range - Screw as wells as DIN Rail fixing (#)

(#) Available on request Busbar / Stud Mounting
In White / Grey Body

Low Voltage BS88 - Clip on Type of Fuses


240 / 550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Breaking Capacity (kA)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	E1	SMALL CLIP	240	33	2	SSD2	70	20	20	N
		ON	240	33	4	SSD4	70	20	20	N
			240	33	6	SSD6	70	20	20	N
			240	33	10	SSD10	70	20	20	N
			240	33	16	SSD16	75	20	20	N
			240	33	20	SSD20	75	20	20	N
			240	33	25	SSD25	80	20	20	O
	F1	CLIP ON	550	80	2	NSD2	60	20	20	N
		TAG	550	80	4	NSD4	60	20	20	N
			550	80	6	NSD6	60	20	20	N
			550	80	10	NSD10	60	20	20	N
			550	80	16	NSD16	70	20	20	N
			550	80	20	NSD20	70	20	20	N
			550	80	25	NSD25	70	20	20	N
	F2	LONG CLIP	550	80	2	ESD2	100	20	20	O
		ON	550	80	4	ESD4	100	20	20	O
			550	80	6	ESD6	100	20	20	O
			550	80	10	ESD10	100	20	20	O
			550	80	16	ESD16	100	20	20	O
			550	80	20	ESD20	100	20	20	O
			550	80	25	ESD25	105	20	20	O
			550	80	32	ESD32	105	20	20	O
			550	80	40	ESD40	135	20	20	O
	550	80	50	ESD50	135	20	20	N		
	550	80	63	ESD63	135	20	20	N		

N - Normal; O - On Order

Effective 1st March, 2022



Low Voltage BS88 Type of fuses

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA

660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFF SET TAG	660 / 690	2	2HO7-660	100	20	20	N	TIA
		CLOSED SLOT	660 / 690	4	4HO7-660	105	20	20	N	
			660 / 690	6	6HO7-660	105	20	20	N	
			660 / 690	10	10HO7-660	105	20	20	N	
			660 / 690	16	16HO7-660	115	20	20	N	
			660 / 690	20	20HO7-660	115	20	20	N	
			660 / 690	25	25HO7-660	120	20	20	N	
			660 / 690	32	32HO7-660	120	20	20	N	
	A3	OFF SET TAG	660 / 690	35	35KO7-660	175	20	20	N	TIS
		CLOSED SLOT	660 / 690	40	40KO7-660	175	20	20	N	
			660 / 690	50	50KO7-660	190	20	20	N	
			660 / 690	63	63KO7-660	190	20	20	N	
	A4	OFF SET TAG	660 / 690	80	80L14-660	315	10	10	N	TCP
		CLOSED SLOT	660 / 690	100	100L14-660	315	10	10	N	
	-	OFF SET TAG	660 / 690	125	125M14-660	640	5	5	N	TFP
		CLOSED SLOT	660 / 690	160	160M14-660	685	5	5	N	
			660 / 690	200	200M14-660	710	5	5	N	

N - Normal; O - On Order

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA



660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660 / 690	80	80LO9-660	355	10	10	O	TC
		SINGLE SLOT	660 / 690	100	100LO9-660	360	10	10	N	
	B2	CENTRE TAG	660 / 690	125	125MO9-660	695	5	5	N	TF
		SINGLE SLOT	660 / 690	160	160MO9-660	710	5	5	N	
			660 / 690	200	200MO9-660	780	5	5	N	
	B3	CENTRE TAG	660 / 690	250	250NO9-660	1310	1	1	N	TKF
SINGLE SLOT		660 / 690	315	315NO9-660	1330	1	1	N		
	C1	CENTRE TAG	660 / 690	355	355P11-660	1620	1	1	O	TMF
		DOUBLE SLOT	660 / 690	400	400P11-660	1665	1	1	O	
	C2	CENTRE TAG	660 / 690	450	450R11-660	1870	1	1	O	TM
		DOUBLE SLOT	660 / 690	500	500R11-660	1945	1	1	O	
			660 / 690	560	560R11-660	2195	1	1	O	TTM
			660 / 690	630	630R11-660	2335	1	1	O	

N - Normal; O - On Order

Effective 1st March, 2022

Low Voltage BS88 Type of fuses


Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class		
	-	OFFSET TAG	550	2	NITD2	90	20	20	N	NIT	
		OPEN SLOT	550	4	NITD4	90	20	20	N		
			550	6	NITD6	90	20	20	N		
			550	10	NITD10	90	20	20	N		
			550	16	NITD16	90	20	20	N		
			550	20	NITD20	90	20	20	N		
			550	25	NITD25	95	20	20	O		
			550	32	NITD32	95	20	20	O		
	A2	OFFSET TAG	550	2	AAO2	80	20	20	N	TSA	
		CLOSED SLOT	550	4	AAO4	80	20	20	O		
			550	6	AAO6	80	20	20	N		
			550	10	AAO10	80	20	20	N		
			550	16	AAO16	80	20	20	N		
			550	20	AAO20	90	20	20	N		
			550	25	AAO25	90	20	20	N		
			550	32	AAO32	90	20	20	N		
	A3	OFFSET TAG	550	35	BAO35	145	20	20	N	TSS	
		CLOSED SLOT	550	40	BAO40	145	20	20	N		
		(@)	550	50	BAO50	150	20	20	N		
			550	63	BAO63	160	20	20	N		
		-	OFFSET TAG	550	80	OSD80	355	20	20	N	TSDS
			CLOSED SLOT	550	100	OSD100	390	20	20	N	

Note: (@) - KO7 - Open Slot, BAO - Closed Slot

N - Normal; O - On Order

Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class		
	C2	CENTRE TAG	550	450	FF450	2355	1	1	O	TST	
		DOUBLE SLOT	550	500	FF500	2475	1	1	O		
			550	560	FF560	2725	1	1	O		
			550	630	FF630	2970	1	1	O		
	C3	CENTRE TAG	550	710	GF710	3160	1	1	O	TLM	
		DOUBLE SLOT	550	800	GF800	3160	1	1	O		
		-	CENTRE TAG	550	710	GG710	#	1	3	O	TLT
			DOUBLE SLOT	550	800	GG800	#	1	3	O	
				550	1000	GG1000	#	1	3	O	
				550	1250	GG1250	#	1	3	O	



- Price Available on request

N - Normal; O - On Order

Effective 1st March, 2022



Low Voltage BS88 Type of fuses

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	OFFSET TAG	550	2	EITD2	100	20	20	N	EIT
		OPEN SLOT	550	4	EITD4	100	20	20	N	
			550	6	EITD6	100	20	20	N	
			550	10	EITD10	100	20	20	N	
			550	16	EITD16	110	20	20	N	
			550	20	EITD20	110	20	20	N	
			550	25	EITD25	110	20	20	N	
			550	32	EITD32	130	20	20	N	
			415	40	EITD40	130	20	20	N	
			415	50	EITD50	140	20	20	N	
	A4	OFFSET TAG	415	32	CEO32	245	10	10	O	TSD
		CLOSED SLOT	415	40	CEO40	245	10	10	O	
			415	50	CEO50	275	10	10	O	
			415	63	CEO63	275	10	10	O	
			415	80	CEO80	340	10	10	N	
			415	100	CEO100	390	10	10	N	
	-	OFFSET TAG	415	125	DEO125	355	5	5	N	TSFP
		CLOSED SLOT	415	160	DEO160	395	5	5	N	
			415	200	DEO200	435	5	5	O	
	B1	CENTRE TAG	415	80	CD80	360	10	10	O	TSDC
		SINGLE SLOT	415	100	CD100	490	10	10	N	
	B2	CENTRE TAG	415	125	DD125	425	5	5	N	TSF
		SINGLE SLOT	415	160	DD160	445	5	5	N	
			415	200	DD200	470	5	5	N	
	B3 / B4	CENTRE TAG	415	250	ED250	930	1	1	N	TSF/ TSK
		SINGLE SLOT								
	B3/B4	CENTRE TAG	415	315	ED315	1025	1	1	N	TSK
		SINGLE SLOT								
B4	CENTRE TAG	415	355	ED355	1065	1	1	O	TSK/ TSM	
	SINGLE SLOT	415	400	ED400	1095	1	1	N		

N - Normal; O - On Order

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	CENTRE TAG	415	355	355SN11(S)	1280	1	1	O	TSMS
		SINGLE SLOT	415	400	400SN11(S)	1320	1	1	N	
	-	CENTRE TAG	415	450	450SP11(S)	1610	1	1	O	TSTS
		SINGLE SLOT	415	500	500SP11(S)	1860	1	1	O	
	-	CENTRE TAG	415	560	560SR11(S)	2475	1	1	O	TSLS
		SINGLE SLOT	415	630	630SR11(S)	2845	1	1	N	
			415	710	710SR11(S)	-	1	1	O	
			415	800	800SR11(S)	3160	1	1	N	
	C1	CENTRE TAG	415	355	EF355	2105	1	1	O	TSM
		DOUBLE SLOT	415	400	EF400	2170	1	1	O	
	-	CENTRE TAG	415	710	710SR11	3550	1	1	O	TSL
		DOUBLE SLOT	415	800	800SR11	3950	1	1	N	

N - Normal; O - On Order

Effective 1st March, 2022

Low Voltage DIN Type, NH Dual Indicator Fuse Links

Rated Voltage 500 Volts AC, Breaking Capacity - 120 kA

500 Vac	Size	Rated Current (A)	Class gL-gG with Dual Indication & Metal Grips	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	000	2	2NHG000B	395	3	3	N	
		4	4NHG000B	395	3	3	N	
		6	6NHG000B	395	3	3	N	
		10	10NHG000B	395	3	3	N	
		16	16NHG000B	395	3	3	N	
		20	20NHG000B	420	3	3	N	
		25	25NHG000B	420	3	3	N	
		32	32NHG000B	420	3	3	N	
		35	35NHG000B	420	3	3	O	
		40	40NHG000B	465	3	3	N	
		50	50NHG000B	465	3	3	N	
		63	63NHG000B	465	3	3	N	
	80	80NHG000B	480	3	3	N		
	100	100NHG000B	495	3	3	N		
	00	63	63NHG00B	480	3	3	N	
		80	80NHG00B	520	3	3	N	
		100	100NHG00B	520	3	3	N	
		125	125NHG00B	520	3	3	N	
		160	160NHG00B	545	3	3	O	
		0 [®]	50	50NHG0B	610	3	3	O
63			63NHG0B	640	3	3	O	
80			80NHG0B	685	3	3	O	
100	100NHG0B		705	3	3	O		
125	125NHG0B		720	3	3	O		
0s	160	160NHG0B	720	3	3	O		
	01 [®]	100	100NHG01B	735	3	3	O	
		125	125NHG01B	755	3	3	O	
		160	160NHG01B	780	3	3	O	
	1	200	200NHG1B	785	3	3	N	
		224	224NHG1B	785	3	3	O	
		250	250NHG1B	850	3	3	N	
		315 [#]	315NHG1B [#]	1050	3	3	O	
		355	355NHG1B	1070	3	3	O	
		02	35	35NHG02B	800	3	3	O
			40	40NHG02B	840	3	3	O
	50		50NHG02B	840	3	3	O	
	63		63NHG02B	840	3	3	O	
	80		80NHG02B	865	3	3	O	
	100		100NHG02B	885	3	3	O	
	125		125NHG02B	905	3	3	O	
	160		160NHG02B	920	3	3	O	
	200		200NHG02B	935	3	3	O	
	224		224NHG02B	935	3	3	O	
	2	250	250NHG02B	960	3	3	O	
		315	315NHG2B	1095	3	3	N	
355		355NHG2B	1110	3	3	O		
400		400NHG2B	1125	3	3	N		
03	250	250NHG03B	1485	3	3	O		
	315	315NHG03B	1515	3	3	O		
	355	355NHG03B	1540	3	3	O		
	400	400NHG03B	1605	3	3	O		
3	425	425NHG3B	1630	3	3	O		
	450	450NHG3B	1630	3	3	O		
	500	500NHG3B	1730	3	3	N		
	630	630NHG3B	1790	3	3	N		
	800 [#]	800NHG3B [#]	2285	3	3	N		

@ Size "0", 6A - 63A on request
Size "1" 80A-160A on request
Insulated grip version available on request

Size "01", 6A - 80A on request
Rated Voltage 440V
500/ 630/ 800/ 1000/ 1250 Amp | 500 V | Size 4 available on request

* Available in Single Indicator type only

N - Normal; O - On Order

Effective 1st March, 2022

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 240 Volts AC, Breaking Capacity - 200 kA

240 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	240	6	6LCT	210	20	20	N
	240	10	10LCT	210	20	20	N
	240	12	12LCT	210	20	20	O
	240	16	16LCT	210	20	20	N
	240	20	20LCT	210	20	20	N
	240	25	25LET	380	10	10	N
	240	32	32LET	400	10	10	N
	240	35	35LET	400	10	10	O
	240	50	50LET	420	10	10	N
	240	63	63LET	420	10	10	N
	240	80	80LET	445	10	10	N
	240	100	100LET	445	10	10	O
	240	125	125LET	465	10	10	N
	240	160	160LET	485	10	10	N
		240	180	180LET	515	10	10
240		160	160LMT	770	1	1	N
240		200	200LMT	815	1	1	N
240		250	250LMT	995	1	1	N
240		315	315LMT	1405	1	1	N
240		355	355LMT	1495	1	1	N
240		400	400LMT	1580	1	1	N
	240	450	450LMT	1815	1	1	N
	240	400	400LMMT	2105	1	1	O
	240	500	500LMMT	2285	1	1	O
	240	630	630LMMT	2510	1	1	O
	240	710	710LMMT	2650	1	1	O
	240	800	800LMMT	3155	1	1	O
240	900	900LMMT	3530	1	1	O	

N - Normal; O - On Order

Rated Voltage 240 Volts AC, Breaking Capacity - 200 kA









240 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	6	6CT	215	20	20	N
	690	10	10CT	215	20	20	N
	690	12	12CT	215	20	20	O
	690	16	16CT	235	20	20	N
	690	20	20CT	235	20	20	N
		690	15	15ET	460	10	10
690		25	25ET	460	10	10	N
690		32	32ET	460	10	10	N
690		35	35ET	460	10	10	N
690		40	40ET	460	10	10	N
690		45	45ET	460	10	10	N
690		56	56ET	515	10	10	N
690		63	63ET	515	10	10	N
690		80	80ET	520	10	10	N

N - Normal; O - On Order

Effective 1st March, 2022

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 690 Volts AC / 240 Volts DC, Breaking Capacity - 200 kA

690 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	35	35FE	495	10	10	N
	690	40	40FE	495	10	10	O
	690	45	45FE	495	10	10	N
	690	50	50FE	495	10	10	N
	690	63	63FE	555	10	10	N
	690	71	71FE	570	10	10	O
	690	80	80FE	615	10	10	N
	690	90	90FE	730	10	10	N
	690	100	100FE	730	10	10	N
	690	75	75EET	1105	5	5	O
	690	90	90EET	1105	5	5	N
	690	110	110EET	1105	5	5	N
	690	140	140EET	1105	5	5	N
	690	160	160EET	1130	5	5	N
	690	100	100FEE	1155	5	5	N
	690	120	120FEE	1210	5	5	N
	690	140	140FEE	1250	5	5	N
	690	160	160FEE	1270	5	5	N
	690	180	180FEE	1300	5	5	O
	690	200	200FEE	1340	5	5	N
	690	160	160MT	985	1	1	N
	690	180	180MT	1030	1	1	N
	690	200	200MT	1295	1	1	N
	690	250	250MT	1320	1	1	N
	690	280	280MT	1420	1	1	N
	690	315	315MT	1855	1	1	N
	690	355	355MT	1890	1	1	N
	690	180	180MMT	1840	1	1	N
	690	200	200MMT	1930	1	1	N
	690	225	225MMT	1990	1	1	N
	690	280	280MMT	2045	1	1	N
	690	315	315MMT	2040	1	1	N
	690	355	355MMT	2350	1	1	N
	690	400	400MMT	2445	1	1	N
	690	450	450MMT	2635	1	1	N
	690	500	500MMT	2920	1	1	N
	690	560	560MMT	3200	1	1	N
	690	630	630MMT	3320	1	1	N
	690	710	710MMT	3805	1	1	N
		690	180	180FM	1030	1	1
690		200	200FM	1160	1	1	N
690		225	225FM	1215	1	1	N
690		250	250FM	1230	1	1	N
690		280	280FM	1380	1	1	O
690		315	315FM	1885	1	1	N
690		350	350FM	1955	1	1	N
690		400	400FMM	2100	1	1	N
	690	450	450FMM	2190	1	1	N
	690	500	500FMM	2470	1	1	N
	690	550	550FMM	2635	1	1	N
	690	630	630FMM	3080	1	1	N
	690	700	700FMM	3395	1	1	N

N - Normal; O - On Order

Effective 1st March, 2022

Accessories

Catalogue No. / Type	Trip Indicator accessory pack (each consists of 1 pair of clip & appropriate size Trip Indicator Fuse Link)	MRP (₹)	Pack Quantity	Delivery Class
EC-250	For use with LET	920	1 set	O
EC-600	For use with ET, EET, FE & FEE	990	1 set	O
MC-250	For use with LMT & LMMT	920	1 set	O
MC-600	For use with FM & FMM	990	1 set	O
MC-700	For use with MT & MMT	1035	1 set	O

Catalogue No. / Type	Micro - Switch	MRP (₹)	Pack Quantity	Delivery Class
MAI	Micro-switch & Adapter assly.	1200	1	O
MBI	Micro-switch & Adapter assly.	#	1	O

- Price Available on request

Catalogue No. / Type	Fuse Clips for Fitting Trip Indicator	MRP (₹)	Pack Quantity	Delivery Class
ECLIP	For use with LET, ET, EET, FE & FEE	155	10	O
MCLIP	For use with LMT, LMMT, MT, MMT, FM & FMM	345	10	O
CL1	Back connected Clip for use with Trip Indicator fuse	1155	1 set	O

Catalogue No. / Type	Trip Indicators for Fuse Links	MRP (₹)	Pack Quantity	Delivery Class
TI250-BT	For use with LET, LMT & LMMT	895	10	O
TI500-BT	For use with ET, EET, FE & FEE, FM & FMM	920	1	O
TI600-BT	For use with ET, EET, FE & FEE, FM & FMM	965	1	O
TI700-BT	For use with MT & MMT	1145	1	O
TI1100-BT	For replacement only	1275	1	O
TI1500-BT	For replacement only	1320	1	O
TI2000-BT	For replacement only	1450	1	O

- Price Available on request

N - Normal; O - On Order

NH Fuse base

Catalogue No. / Type	Fuse Accessories	MRP (₹)	Pack Quantity	Delivery Class
SD1-S	NH Fuse base 250A, 690VAC DIN Size 1 (Screw Mounting)	1010	3	O
SD2-S	NH Fuse base 400A, 690VAC DIN Size 2 (Screw Mounting)	1490	3	O
SD3-S	NH Fuse base 630A, 690VAC DIN Size 3 (Screw Mounting)	2160	3	O
SD4-S	NH Fuse base 1250A, 690VAC DIN Size 4 (Screw Mounting)	4890	1	O

N - Normal; O - On Order

British Standard Type Range of Fuses for use in Air.

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
		3.3 / 3.6	25	15	3.6ADGHC15	3895	1	1	O
		3.3 / 3.6	25	20	3.6ADGHC20	3895	1	1	O
		3.3 / 3.6	25	25	3.6ADGHC25	3895	1	1	O
		3.3 / 3.6	25	30	3.6ADGHC30	3895	1	1	O
		3.3 / 3.6	25	40	3.6ADGHC40	3895	1	1	O
		3.3 / 3.6	25	45	3.6ADGHC45	3895	1	1	O
		3.3 / 3.6	25	50	3.6ADGHC50	3895	1	1	O
		3.3 / 3.6	25	60	3.6ADGHC60	3895	1	1	O
		3.3 / 3.6	25	70	3.6ADGHC70	3895	1	1	O
		3.3 / 3.6	25	75	3.6ADGHC75	4315	1	1	O
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	10	7.2BDGHC10	3940	1	1	O
		6.6 / 7.2	40	16	7.2BDGHC16	3940	1	1	O
		6.6 / 7.2	40	20	7.2BDGHC20	3940	1	1	O
		6.6 / 7.2	40	25	7.2BDGHC25	3940	1	1	O
		6.6 / 7.2	40	31.5	7.2BDGHC31.5	3940	1	1	O
		6.6 / 7.2	40	35.5	7.2BDGHC35.5	3940	1	1	O
		6.6 / 7.2	40	40	7.2BDGHC40	3940	1	1	O
		6.6 / 7.2	40	45	7.2BDGHC45	4010	1	1	O
		6.6 / 7.2	40	50	7.2BDGHC50	4010	1	1	O
		6.6 / 7.2	40	56	7.2BDGHC56	4010	1	1	O
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	60	7.2BDGHC60	4010	1	1	O
		6.6 / 7.2	40	63	7.2BDGHC63	4265	1	1	O
		6.6 / 7.2	40	71	7.2BDGHC71	4295	1	1	O
		6.6 / 7.2	40	80	7.2BDGHC80	4295	1	1	O
		6.6 / 7.2	40	50	7.2AHGHC50	4815	1	1	O
		6.6 / 7.2	40	60	7.2AHGHC60	4905	1	1	O
		6.6 / 7.2	40	75	7.2AHGHC75	5165	1	1	O
		6.6 / 7.2	40	90	7.2AHGHC90	5455	1	1	O
		6.6 / 7.2	40	100	7.2AHGHC100	5485	1	1	O
		6.6 / 7.2	40	112	7.2AHGHC112	6365	1	1	O
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	125	7.2AHGHC125	6615	1	1	O
		6.6 / 7.2	40	140	7.2AHGHC140	7215	1	1	O
		6.6 / 7.2	40	150	7.2AHGHC150	7215	1	1	O
		6.6 / 7.2	40	160	7.2AHGHC160	7420	1	1	N
		6.6 / 7.2	40	160	7.2AHGNB160 (NS)	6910	1	1	O
		6.6 / 7.2	40	50	7.2AHGHB50	4745	1	1	O
		6.6 / 7.2	40	60	7.2AHGHB60	4745	1	1	O
		6.6 / 7.2	40	65	7.2AHGHB65	4995	1	1	O
		6.6 / 7.2	40	75	7.2AHGHB75	5050	1	1	O
		6.6 / 7.2	40	90	7.2AHGHB90	5285	1	1	N
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	100	7.2AHGHB100	5310	1	1	O
		6.6 / 7.2	40	112	7.2AHGHB112	6165	1	1	O
		6.6 / 7.2	40	120	7.2AHGHB120	6415	1	1	O
		6.6 / 7.2	40	125	7.2AHGHB125	6415	1	1	O
		6.6 / 7.2	40	140	7.2AHGHB140	7005	1	1	O
		6.6 / 7.2	40	150	7.2AHGHB150	7005	1	1	O
		6.6 / 7.2	40	160	7.2AHGHB160	7005	1	1	O
		6.6 / 7.2	20	30	7.2AEFMO30	4935	1	1	O
		6.6 / 7.2	20	35	7.2AEFMO35	4935	1	1	O
		6.6 / 7.2	20	40	7.2AEFMO40	4935	1	1	O
6.6 / 7.2	20	50	7.2AEFMO50	4985	1	1	O		
6.6 / 7.2	20	56	7.2AEFMO56	4985	1	1	O		
6.6 / 7.2	20	63	7.2AEFMO63	4985	1	1	O		
6.6 / 7.2	20	71	7.2AEFMO71	5010	1	1	O		
6.6 / 7.2	20	80	7.2AEFMO80	5010	1	1	O		
6.6 / 7.2	20	90	7.2AEFMO90	5115	1	1	O		

(#) Available on request
(NS) Non striker

N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot9

- 1 - For BD _____ series, add "S" at the end of the cat. number. For ex : For ordering 100A, 7.2BFGHD catalogue no. will be "7.2BFGHD100S"
- 2 - For AH _____ series, replace "C" at end with "B" For ex : For ordering 100A, 7.2AHGH series, catalogue no. will be "7.2AHGHB100"
- 3 - For "7.2BFGHD" ___ series, completely replaced with "7.2AHGHB".

Effective 1st March, 2022

British Standard Type Range of Fuses for use in Air.

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Air	11 / 12	40	6.3	12BDGHC6.3	4635	1	1	O
		11 / 12	40	10	12BDGHC10	4635	1	1	O
		11 / 12	40	16	12BDGHC16	4635	1	1	O
		11 / 12	40	20	12BDGHC20	4390	1	1	O
		11 / 12	40	25	12BDGHC25	4240	1	1	N
		11 / 12	40	31.5	12BDGHC31.5	4265	1	1	O
		11 / 12	40	35.5	12BDGHC35.5	4265	1	1	O
		11 / 12	40	40	12BDGHC40	4295	1	1	O
		11 / 12	40	45	12BDGHC45	4295	1	1	O
	Air (Bus Duct / Distribution)	11 / 12	40	50	12BDGHC50	4330	1	1	O
		11 / 12	40	56	12AHGHC56	4955	1	1	O
		11 / 12	40	63	12AHGHC63	4955	1	1	N
		11 / 12	40	70	12AHGHC70	5020	1	1	O
		11 / 12	40	80	12AHGHC80	5435	1	1	N
		11 / 12	40	90	12AHGHC90	5390	1	1	O
		11 / 12	40	100	12AHGHC100	5435	1	1	O
		11 / 12	40	56	12AHGHB56	4980	1	1	O
		11 / 12	40	63	12AHGHB63	5025	1	1	N
		11 / 12	40	65	12AHGHB65	5230	1	1	O
		11 / 12	40	70	12AHGHB70	5230	1	1	N
		11 / 12	40	80	12AHGHB80	5470	1	1	O
	Air (Bus Duct / Distribution)	11 / 12	40	90	12AHGHB90	5580	1	1	O
		11 / 12	40	100	12AHGHB100	5580	1	1	N
		11 / 12	40	112	12AKGHD112	12660	3	3	O
		11 / 12	40	125	12AKGHD125	12750	1	1	O
		11 / 12	20	3.7	12AEFMO3.7	4970	1	1	O
		11 / 12	20	12	12AEFMO12	4920	1	1	O
		11 / 12	20	15	12AEFMO15	4920	1	1	O
		11 / 12	20	16.8	12AEFMO16.8	4920	1	1	O
		11 / 12	20	22	12AEFMO22	4950	1	1	O
		11 / 12	20	26.6	12AEFMO26.6	4950	1	1	O
		11 / 12	20	30	12AEFMO30	4950	1	1	O
		11/12	20	33.75	12AEFMO33.75	4950	1	1	O
		11 / 12	20	37.5	12AEFMO37.5	4950	1	1	O
11 / 12	20	42	12AEFMO42	5000	1	1	O		
11 / 12	20	47.25	12AEFMO47.25	5000	1	1	O		

(#) Available on request



N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot -
1 - For "12BFGHD" _ _ _ series, completely replaced with "12AHGHB".

Effective 1st March, 2022




High Voltage Fuses

For use in Oil

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Oil	6.6 / 7.2	45	100	7.2OEFMA100	4500	1	1	O
	Oil	11 / 12	40	6.3	12OEFMA6.3	4895	3	3	O
		11 / 12	40	10	12OEFMA10	5410	3	3	O
		11 / 12	40	16	12OEFMA16	5410	3	3	O
		11 / 12	40	20	12OEFMA20	5425	3	3	O
		11 / 12	40	25	12OEFMA25	5425	3	3	O
		11 / 12	40	31.5	12OEFMA31.5	5425	3	3	O
		11 / 12	40	40	12OEFMA40	5440	3	3	O
		11 / 12	40	50	12OEFMA50	5440	3	3	O
		11 / 12	40	63	12OEFMA63	5440	3	3	O
11 / 12		40	71	12OHFMA71	5625	3	3	O	
11 / 12		40	80	12OHFMA80	5625	3	3	O	
		11 / 12	40	16	12OHGMA16	6605	3	3	O
		11 / 12	40	25	12OHGMA25	6640	3	3	O
		11 / 12	40	31.5	12OHGMA31.5	6640	3	3	O
		11 / 12	40	40	12OHGMA40	6675	3	3	O
		11 / 12	40	50	12OHGMA50	6675	3	3	O
		11 / 12	40	63	12OHGMA63	6675	3	3	O
		11 / 12	40	80	12OHGMA80	6675	3	3	O
		11 / 12	40	90	12OHGMA90	6930	3	3	O
	11 / 12	40	100	12OHGMA100	7570	3	3	O	
	11 / 12	40	125	12OLGMA125	8510	3	3	O	

N - Normal; O - On Order



For use in PT / VT & Auxiliary Transformer

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNA3.15	980	1	1	N
		3.3 / 3.6	50	6.3	3.6ABWNA6.3	980	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNA3.15	1070	1	1	N
		6.6 / 7.2	45	6.3	7.2ABCNA6.3	1070	1	1	O
		6.6 / 7.2	45	3.15	7.2ABWNA3.15	1055	1	1	O
		6.6 / 7.2	45	6.3	7.2ABWNA6.3	1055	1	1	O
		11 / 12	45	3.15	12ABCNA3.15	1080	1	1	N
		22 / 24	25	3.15	24ABGNA3.15	2475	1	1	N
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNS3.15	1055	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNS3.15	1165	1	1	O
		11 / 12	45	3.15	12ABCNS3.15	1255	1	1	O
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNT3.15	1200	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNT3.15	1100	1	1	O
		11 / 12	45	3.15	12ABCNT3.15	1270	1	1	O

N - Normal; O - On Order

Effective 1st March, 2022

British Standard Type Range of Fuses for use in Motor Circuits


	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	For use in MV Motor Circuits	3.6	50	5	3.6WDOHS5	4320	1	1	O
		3.6	50	16	3.6WDOHS16	4320	1	1	O
		3.6	50	20	3.6WDOHS20	4320	1	1	N
		3.6	50	25	3.6WDOHS25	4320	1	1	O
		3.6	50	32	3.6WDOHS32	4275	1	1	N
		3.6	50	40	3.6WDOHS40	4275	1	1	O
		3.6	50	50	3.6WDOHS50	4325	1	1	O
		3.6	50	63	3.6WDOHS63	4360	1	1	N
		3.6	50	80	3.6WDOHS80	4360	1	1	O
		3.6	50	50	3.6WDFMO50	6135	1	1	O
		3.6	50	63	3.6WDFMO63	6310	1	1	O
		3.6	50	80	3.6WDFMO80	6310	1	1	O
		3.6	50	100	3.6WDFMO100	6310	1	1	O
		3.6	50	100	3.6WFFMO100	7910	1	1	O
		3.6	50	140	3.6WFFMO140	8820	1	1	O
		3.6	50	160	3.6WFFMO160	9065	1	1	O
		3.6	50	200	3.6WFFMO200	9825	1	1	N
		3.6	50	250	3.6WFFMO250	11135	1	1	O
		3.6	50	315	3.6WFFMO315	12860	1	1	O
		3.6	50	350	3.6WFFMO350	14235	1	1	O
3.6	50	450	3.6WFFMO450	21400	1	1	O		
3.6	50	630	3.6WKFM0630	27435	1	1	O		
	For use in MV Motor Circuits	7.2	45	50	7.2WFNMO50	8805	1	1	O
		7.2	45	63	7.2WFNMO63	8805	1	1	O
		7.2	45	80	7.2WFNMO80	10400	1	1	O
		7.2	45	100	7.2WFNMO100	10400	1	1	O
		7.2	45	125	7.2WFNMO125	12025	1	1	O
		7.2	45	160	7.2WFNMO160	12140	1	1	O
		7.2	45	200	7.2WFNMO200	13895	1	1	O
		7.2	45	250	7.2WFNMO250	16430	1	1	O
		7.2	45	50	7.2WFQMO50	9595	1	1	N
		7.2	45	63	7.2WFQMO63	9685	1	1	N
		7.2	45	80	7.2WFQMO80	10730	1	1	N
		7.2	45	100	7.2WFQMO100	11390	1	1	N
		7.2	45	125	7.2WFQMO125	13285	1	1	N
		7.2	45	160	7.2WFQMO160	13405	1	1	O
		7.2	45	200	7.2WFQMO200	15120	1	1	O
		7.2	45	250	7.2WFQMO250	18730	1	1	O
		7.2	45	350	7.2WKQMO350	25295	1	1	O
		7.2	45	400	7.2WKQMO400	42620	1	1	O

N - Normal; O - On Order

Effective 1st March, 2022

BS Fuse link Type SS/NS/ES


Clip-on Fuse links with Staggered Tags-415 V AC

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	E1	SMALL CLIP ON TAG	415	2	SS2	80	20	20	O	SSD
			415	4	SS4	80	20	20	N	
		415	6	SS6	80	20	20	N		
		415	10	SS10	80	20	20	O		
		415	16	SS16	85	20	20	O		
		415	20	SS20	85	20	20	O		
	F1	CLIP ON TAG	415	2	NS2	115	20	20	N	NSD
			415	4	NS4	115	20	20	N	
		415	6	NS6	115	20	20	N		
		415	10	NS10	115	20	20	N		
		415	16	NS16	115	20	20	N		
		415	20	NS20	135	20	20	N		
		415	25	NS25	135	20	20	N		
		415	32	NS32	135	20	20	N		
	F2	LONG CLIP ON TAG	415	2	ES2	110	20	20	O	ESD
			415	4	ES4	110	20	20	O	
		415	6	ES6	110	20	20	O		
		415	10	ES10	110	20	20	O		
		415	16	ES16	110	20	20	O		
		415	20	ES20	110	20	20	O		
		415	25	ES25	115	20	20	O		
		415	32	ES32	115	20	20	O		
		415	36	ES36	115	20	20	O		
		415	50	ES50	155	20	20	N		
		415	63	ES63	160	20	20	N		

N - Normal; O - On Order

BS Fuse link Type EIT.

Fuse link with Offset Tags



415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
		OFFSET TAG	415	2	EIT2	125	20	20	O	EITD
		OPEN SLOT	415	4	EIT4	125	20	20	O	
		415	6	EIT6	125	20	20	N		
		415	10	EIT10	125	20	20	N		
		415	16	EIT16	125	20	20	N		
		415	20	EIT20	130	20	20	N		
		415	25	EIT25	130	20	20	N		
		415	32	EIT32	130	20	20	N		
		415	36	EIT36	155	20	20	O		
		415	50	EIT50	155	20	20	O		
		415	63	EIT63	160	20	20	N		

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Effective 1st March, 2022


Fuse link with Offset Tags Closed Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFFSET TAG	415	6	TSA6	135	20	20	O	AAO
		CLOSED SLOT	415	10	TSA10	135	20	20	O	
			415	16	TSA16	135	20	20	N	
			415	20	TSA20	135	20	20	O	
			415	25	TSA25	135	20	20	N	
			415	32	TSA32	135	20	20	N	
	A3	OFFSET TAG	415	36	TSS36	160	20	20	N	BAO
		CLOSED SLOT	415	50	TSS50	280	20	20	N	
			415	63	TSS63	280	20	20	N	
	-	OFFSET TAG	415	80	TSDS80	400	10	10	N	OSD
		CLOSED SLOT	415	100	TSDS100	400	10	10	N	
			415	125	TSDS125	400	10	10	N	
	A4	OFFSET TAG	415	80	TSD80	280	10	10	N	CEO
		CLOSED SLOT	415	100	TSD100	295	10	10	N	
			415	125	TSD125	655	10	10	N	
-	OFFSET TAG	415	125	TSFP125	655	10	10	O	DEO	
	CLOSED SLOT	415	160	TSFP160	655	10	10	N		
		415	200	TSFP200	655	10	10	O		

N - Normal; O - On Order

Type - TSDC \ TSK \ TSMS \ TSTS \ TSL

Fuse Links with Centre Tag Single Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	Centre Tag	415	80	TSDC80	490	10	10	O	CD
		Single Slot	415	100	TSDC100	490	10	10	N	
	B3	Centre Tag	415	250	TSK250	1230	10	10	N	ED
		Single Slot	415	315	TSK315	1230	10	10	N	
	C1	Centre Tag	415	355	TSMS355	1200	1	1	O	SN11(S)
		Single Slot	415	400	TSMS400	1425	1	1	N	
	-	Centre Tag	415	450	TSTS450	2020	1	1	O	SP11(S)
		Single Slot	415	500	TSTS500	2020	1	1	O	
	-	Centre Tag	415	560	TSL560	3260	1	1	O	SR11(S)
		Single Slot	415	630	TSL5630	3260	1	1	O	
			415	710	TSL5710	3035	1	1	O	SR11(S)
			415	750	TSL5750	3050	1	1	O	
			415	800	TSL5800	4705	1	1	N	


Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Effective 1st March, 2022

Type - TSM / TST / TSL


Fuse link with Offset Tags Double Slot.

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class		
	C1	Centre Tag	415	355	TSM355	2160	1	1	O	EF	
		Double Slot	415	400	TSM400	2160	1	1	O		
	C2	Centre Tag	415	450	TST450	1785	1	1	O	FF	
		Double Slot	415	500	TST500	3405	1	1	O		
	C3	Centre Tag		415	560	TSL560	3260	1	1	O	SR11
			Double Slot	415	630	TSL630	3360	1	1	N	
			415	710	TSL710	3360	1	1	O		
			415	750	TSL750	3365	1	1	O		
			415	800	TSL800	3560	1	1	N		

N - Normal; O - On Order

Type - TM \ TTM \ TLM


Fuse Links with Centre Tags Double Slot

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class		
	C1	Centre Tag	660	355	TM355	2030	1	1	O	SP11	
		Double Slot	660	400	TM400	2105	1	1	O		
	C2	Centre Tag		660	450	TTM450	2370	1	1	O	R11
			Double Slot	660	500	TTM500	2470	1	1	O	
				660	560	TTM560	2765	1	1	O	
	C3	Centre Tag		660	630	TTM630	2880	1	1	O	GF
			Double Slot	660	630	TLM630	5135	1	1	O	
			660	710	TLM710	5135	1	1	O		
		660	750 & 800	TLM750 & 800	5135	1	1	O			

N - Normal; O - On Order

Type TIA \ TIS \ TCP \ TFP


Fuse with Offset Tags (2 hole fixing - Bolted)

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class			
	A2	OFFSET TAG	660	2	TIA2	135	10	10	O	HO7		
		CLOSED SLOT		660	4	TIA4	135	10	10		O	
				660	6	TIA6	165	10	10		N	
				660	10	TIA10	165	10	10		N	
				660	16	TIA16	165	10	10		N	
				660	20	TIA20	165	10	10		N	
				660	25	TIA25	165	10	10		N	
				660	32	TIA32	165	10	10		N	
	A3	OFFSET TAG	660	36	TIS36	215	10	10	N	KO7		
		CLOSED SLOT		660	40	TIS40	280	10	10		O	
				660	50	TIS50	235	10	10		N	
				660	63	TIS63	235	10	10		N	
	A4	OFFSET TAG	660	80	TCP80	660	6	6	N	L14		
		CLOSED SLOT	660	100	TCP100	660	6	6	N			
				660	125	TFP125	1045	3	3	O	M14	
				660	160	TFP160	1045	3	3	O		
				660	200	TFP200	1045	3	3	O		

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

Effective 1st March, 2022

Fuse with Central Tags

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660	80	TC80	705	6	6	O	LO9
		SINGLE SLOT	660	100	TC100	705	6	6	N	
			660	80	102TC80	440	6	6	O	
			660	100	102TC100	490	6	6	O	
	B3	CENTRE TAG	660	125	TF125	1135	3	3	N	MO9
		SINGLE SLOT	660	160	TF160	1135	3	3	N	
			660	200	TF200	1135	3	3	N	
			660	250	TF250	660	3	3	N	
	B3	CENTRE TAG	660	250	TKF250	1570	1	1	N	NO9
		SINGLE SLOT	660	315	TKF315	1570	1	1	N	

N - Normal; O - On Order

Moulded Fuse Holder and Fuse Base for 415V AC Circuit

Type - SC (Safe Clip)

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
E1	-	Front	SS	20	SC20H	415	265	10	10	O
F1	-	Front	NS	32	SC32H	415	-	10	10	O
F2	-	Front	ES	63	SC63H	415	510	10	10	N

N - Normal; O - On Order

Fuse Fittings for LV BS Type of Fuses

Type - NS & SM: Moulded Fuse Holder

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1		Front	NS (upto 32A)	32	NSH32	415	265	10	10	N
		Back	NS (upto 32A)	32	NSP32	415	250	10	10	N
		Busbar	NS (upto 32A)	32	NSB32	415	215	10	10	N
A2	Offset Bolted	Front	TIA / TSA	32	SM32H	660	400	10	10	N
		Busbar	TIA / TSA	32	SM32B	660	510	10	10	N
A3	Offset Bolted	Front	TIA / TSS	63	SM63H	660	525	10	10	N
		Busbar	TIA / TSS	63	SM63B	660	585	10	10	N
A4	Offset Bolted	Front	TCP / TSD	125	SM125H	660	1320	5	10	N
		Busbar	TCP / TSD	125	SM125B	660	1455	5	10	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Type GSMJ/GSMK/SMK Ultra-fast Acting Multi Body Fuselink for

Fuselink for Diode & Thyristor Protection

800 \ 1000 Vac	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	800	63	GSMJ63	1050	3	3	O
	800	120	GSMJ120	2435	1	1	O
	800	180	GSMJ180	3660	2	2	O
	800	240	GSMJ240	4770	1	1	O
	800	300	GSMJ300	5460	1	1	O
	800	350	GSMJ350	7180	1	1	O
	800	400	GSMJ400	8425	1	1	O
	800	460	GSMJ460	9260	1	1	O
	800	520	GSMJ520	10250	1	1	O
	800	580	GSMJ580	12280	1	1	O
	800	630	GSMJ630	13735	1	1	O
	800	680	GSMJ680	15185	1	1	O
	800	800	GSMJ800	19565	1	1	O
	800	1000	GSMJ1000	24465	1	1	O
	800	1200	GSMJ1200	27890	1	1	O
	1000	63	GSMK63	530	3	3	O
	1000	120	GSMK120	2560	2	2	O
	1000	180	GSMK180	3745	2	2	O
	1000	240	GSMK240	5360	1	1	O
	1000	300	GSMK300	6145	2	2	O
	1000	350	GSMK350	7600	2	2	O
	1000	400	GSMK400	9160	1	1	O
	1000	460	GSMK460	10190	1	1	O
	1000	520	GSMK520	12385	1	1	O
	1000	580	GSMK580	13320	1	1	O
	1000	630	GSMK630	14885	1	1	O
	1000	680	GSMK680	16340	1	1	O
	1000	800	GSMK800	19935	1	1	O
	1000	1000	GSMK1000	-	1	1	O
	1000	1200	GSMK1200	31630	1	1	O
	-	2000	SMK-GSM120-1200	520	1	1	O
	-	400	954GSMJ400	9520	1	1	O
	1000	500	RGS500	7745	1	1	O

N - Normal; O - On Order

Semiconductor Fuse Accessories

Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
TI300-BI	-	590	20	20	N
TI600-BI	-	625	20	20	N
TI1200-BI	-	635	20	20	N
TI2000-BI	-	715	20	20	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Effective 1st March, 2022

British Standard Type Range of Fuses for use in Motor Circuits

3.6 / 7.2 KV	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	3.6	5	K3PGX5	5605	1	1	O
	3.6	10	K3PGX10	5605	1	1	O
	3.6	16	K3PGX16	5605	1	1	O
	3.6	20	K3PGX20	5605	1	1	O
	3.6	25	K3PGX25	5605	1	1	O
	3.6	32	K3PGX32	5605	1	1	O
	3.6	40	K3PGX40	5605	1	1	O
	3.6	50	K3PGX50	5715	1	1	O
	3.6	63	K3PGX63	5730	1	1	O
	3.6	80	K3PGX80	5730	1	1	O
	3.6	100	K81PEX100	9755	1	1	O
	3.6	160	K81PEX160	10945	1	1	N
	3.6	200	K81PEX200	12350	1	1	O
	3.6	250	K81PEX250	14170	1	1	N
	3.6	315	K81PEX315	17130	1	1	O
	3.6	350	K81PEX350	19765	1	1	N
	7.2	50	K81SVX50	12100	1	1	O
	7.2	63	K81SVX63	12215	1	1	N
	7.2	80	K81SVX80	13310	1	1	N
	7.2	100	K81SVX100	15295	1	1	N
	7.2	125	K81SVX125	16810	1	1	N
	7.2	160	K81SVX160	17125	1	1	O
	7.2	200	K81SVX200	19990	1	1	O
	7.2	250	K81SVX250	24555	1	1	O
	7.2	50	KSVX50	12795	1	1	O
	7.2	63	KSVX63	12795	1	1	O
	7.2	80	KSVX80	13045	1	1	O
	7.2	100	KSVX100	13160	1	1	O
	7.2	125	KSVX125	13285	1	1	O
	7.2	160	KSVX160	15035	1	1	O
	7.2	200	KSVX200	17130	1	1	O
	7.2	250	KSVX250	19580	1	1	O

N - Normal; O - On Order

Cross Reference Chart

LV BS FUSES

Clip on Type

BS Size	Bussmann	Bussmann
E1	SSD	SS
F1	NSD	NS
F2	ESD	ES

Bolted Type - 550V Range

BS Size	Bussmann	Bussmann*
A1	NITD	NIT
A2	AAO	TSA
A3	BAO*	TSS
A4	CEO	TSD
-	OSD	TSDS
C2	FF	TST
C3	GF	TLM
-	GG	TLT

*Fuses are 415V rated

Bolted Type - 660V Range

BS Size	Bussmann	Bussmann
A2	HO7-660	TIA
A3	KO7-660	TIS
A4	L14-660	TCP
-	M14-660	TFP
B1	LO9-660	TC
B2	MO9-660	TF
B3	NO9-660	TKF
B4	PO9-660	TMF
C1	P11-660	TM
C2	R11-660	TTM

Bolted Type - 415V Range

BS Size	Bussmann	Bussmann
-	EITD	EIT
-	DEO	TSFP
B1	CD	TSDC
B2	DD	TSF
B3	ED	TSF/TSK
B4	ED	TSK/TSM
-	SN11(S)	TSMS
-	SP11(S)	TSTS
-	SR11(S)	TSLS
C1	EF	TSM
-	SR11	TSL

HIGHSPEED BS88 FUSES

Bussmann		Bussmann		Brand 4	
TYPE	RANGE	TYPE	RANGE	TYPE	RANGE
240 Volts Range					
LCT	6-20	GSA	5-20	2.5URE	6-20
LET	25-180	GSA	25-100	2.5URGS/URZ	25-100
LMT	160-450	GS450	150-250	2.5URGG	150-250
LMT	160-450	GS450	300-500	2.5URGH	300-500
LMMT	400-900	--	--	--	--
690 Volts Range					
CT	6-20	GSB	5-20	6.6URE	6-20
ET	25-80	GSB	25-75	6.6URS	25-75
ET	25-80	GSG1000	16-55	6.6URS	16-55
EET	90-160	GSG1000	75-150	6.6URT	75-140
FM	180-350	GS1000	100-200	6.6URGL/UR	100-250
MT	160-355	GS1000	100-200	6.6URGL/UR	100-250
MMT	180-710	GS1000	300-500	--	--
MMT	180-710	GSG1000	175-350	6.6URGM/URU	175-350

HV FUSES

Appl. used in	Bussmann	Bussmann	Appl. used in	Bussmann	Bussmann
Air	ADGHC	H2CAS	VT/PT	ABCNS	5xVTF
Air	ADOH6 / ADOH7	K3PGX	Motor Ckt.	WDOHS	K3PGX
Air	BFGHD	H2CAS	Motor Ckt.	WDFMO/ WFFMO	K81PEX/ K81PRX
Air	BDGHC	H2CAS	Motor Ckt.	WKFMO	K82PEX
Air	AHGHC	H2CAS	Motor Ckt.	WFQMO	K81SVX / K81SRX
Oil	OHGMA/OLGMA	KEMXO	Motor Ckt.	WKQMO	K82SSX
Oil	OEFMA/OHFMA	KEBXO			
VT/PT	ABWNA	VTF			
VT/PT	ABCNA	VTF			

LV NH DIN FUSES

Size as per IEC	Bussmann	Bussmann	Brand 2	Brand 3
400 / 415 Volts				
SIZE C00/000	NHG000B-400	NA	NA	
SIZE 00	NHG00B-400	NA	NA	HNSIZE00
SIZE 1	NHG01-400 / NHG1-400	NA	NA	HN SIZE1
SIZE 2	NHG02-400 / NHG2-400	NA	NA	HN SIZE2
SIZE 3	NHG03-400 / NHG3-400	NA	NA	HN SIZE3
500 Volts				
SIZE C00/000	NHG000B	VSA	3NA38	NA
SIZE 00	NHG00B	VSB	3NA10	NA
SIZE 1	NHG01 / NHG1	VSF	3NA12	NA
SIZE 2	NHG02 / NHG2	VSK	3NA13	NA
SIZE 3	NHG03 / NHG3	VST	3NA14	NA
660 / 690 Volts				
SIZE 00	NH00G - 690	NA	NA	NA
SIZE 1	NH1G-690	NA	NA	NA
SIZE 2	NH2G- 690	NA	NA	NA
SIZE 3	NH3G- 690	NA	NA	NA

LV NH DIN Bases

Suitable for Size	Bussmann		Bussmann	Brand 2	Brand 3
	Type	Amps			
C00/000/00	SB 00 - PB	160	ISG160	3NH3030 / 3032	HB 125
01/1	SB 1 - D	250	ISG250	3NH3230	HB 250
02/2	SB 2 - D	400	ISG400	3NH3330	HB 800

LV BS88 Bases

BS Size	Bussmann			Bussmann	Brand 2	Brand 3
	Fuse Types	Type	Amps			
Old Type						
F1	NSD / FO6	FA	32	NSH	NA	HD32H
F1	NSD / FO6	FB	32	NSP	NA	HD32P
F1	NSD / FO6	FD	32	NSB	NA	HD32B
A2	HO7 / AAO / FO7	HA	32	SM32H	NA	HK32H
A2	HO7 / AAO / FO7	HD	32	SM32B	NA	HK32B
A3	TO7 / BAO / KO7	KA	63	SM63H	NA	HK63H
A3	TO7 / BAO / KO7	KD	63	SM63B	NA	HK63B
A4	L14 / CEO / DEO @ / M14 @ / KL14	LA	125	SM125H	NA	HK125H
A4	L14 / CEO / DEO @ / M14 @ / KL14	LD	125	SM125B	NA	HK125B
New Safeloc Type						
F1	NSD / FO6	NNSF	32	SC32H	3NW 32	NA
					NNSF	
F2	ESD	ENSF	63	SC63H	NA	NA
New Range - Cam Master						
A2	HO7 / AAO / FO7	CM32F	32		3NW CM32F9	NA
A3	TO7 / BAO / KO7	CM63F	63		3NW CM63F9	NA
	OSD	CM100F	100		3NW CM100F9	NA

@ - upto 125A only

- ❖ The chart is intended for guidance purpose only, considering physical replacability
- ❖ In identical operating condition, Bussmann fuse can be used to achieve similar performance.
- ❖ Other makes may not necessarily have identical performance. Relevant data like rated voltage, breaking capacity, let thru' current, etc also need to be evaluated while evaluating fuse performance.

Effective 1st March, 2022

Global Technology Regional Solutions

Electrical standards and certifications

PRICE :

- For items marked (#), prices available on request.
- Prices are subject to change without prior notice.
- This Price list supersedes all previous Price Lists.
- Price prevailing at the time of dispatch will only be applicable.
- For prices of any special products not listed here, please contact us
- Prices are Ex-Pondicherry, exclusive of packing, forwarding, freight & insurance.
- Company reserves the right to issue amendments which may arise due to any errors in the Price List

TAXES AND DUTIES :

- All prices in this document are inclusive of GST.

Order Postponement or cancellation is not allowed.
For all shipments, orders to be in multiples of the carton quantity.
All prices are in Rupees (₹) per individual item unless stated otherwise.

This price list is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products or discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this price list. Once a product has been selected, it should be tested by the user in all possible applications. The information contained in this price list is correct at the time of publication, but we reserve the right to supply products differing in construction or performance.



India Head Office
Eaton Power Quality Pvt. Ltd.
2, EVR Street, Sedarpet
Industrial Estate
Pondicherry-605111
Tel: +91 413 2672000
Enquiries - EatonElectricalIndia@eaton.com

www.eaton.com
© 2022 Eaton Corporation All Rights Reserved India

Offices Across India

Mumbai
Eaton Power Quality Pvt. Ltd.
Unit No. 101 & 102 'A' wing,
1st Floor, 215 Atrium, Andheri - Kurla Road,
Andheri (East), Mumbai - 400 093.
Mobile: + 91 8291967878, 9321199760

Chennai
No. 36, Nehru Street,
Old Mahabhalipuram Road,
Sholinganallur, Chennai-600 119, India
Tel: +91 44 66501544/45
Mobile: +91 9840326095

Delhi
Unit A1 & B1, 3rd Floor, TDI Centre
Plot No. 7, Jasola, New Delhi-110025
Tel: +91 11 45851800
Mobile: +91 9811086586

Bangalore
4th Floor, Prestige Atrium, Central Street
Bangalore 560001, India
Tel: +91 80 49012200
Mobile: +91 9916514234,
+919845175290

Kolkata
Mobile: +91 8334008313

Pune
145, Off, Mumbai - Pune Road
Pimpri, Pune-411018
Mobile: +91 9320141508

Vadodara
Mobile: +91 9879355485

Coimbatore
Mobile: +91 9344893165

Hyderabad
Mobile: +91 9533423461

Ahmedabad
Mobile: +91 9879355485

Chandigarh
Mobile: +91 9501177119

Indore
Mobile: +91 9501177119

Cochin
Mobile: +91 9344893165

Regional E-mails

For E-mail, prefix cityname to buss.____@eaton.com
Example, for Delhi, write - bussmandelhi@eaton.com