

Life Is On

Schneider
Electric

DIGITAL

Power

 PriceList

Power Monitoring Solutions Metering Products

With effect from January 27th, 2020

TECHMECHELEC
TECHNICAL MECHANICAL ELECTRICAL



se.com/in

Techmech Electricals
1540-A, Bhagirath Palace, Delhi-06
techmechelec@yahoo.com

www.techmech.yolasite.com

1. Tailored Offers for Specific Applications and Segments	
1.1 BCPM Data Center Management with Information	7
1.2 Vigilohm Range of Insulation Monitoring Devices.....	7
2. High Accuracy, Specialized Solutions - for MV/LV Distribution	
2.1 PowerLogic™ ION9000T NEW	9
2.2 PowerLogic™ ION9000 NEW	9
2.3 PowerLogic™ ION 8800 / 8650	9
2.4 PowerLogic™ PM8000 Series Power Quality Analyser	10
3. High Accuracy, Compact, Power Meters - for MV/LV Distribution	
3.1 PowerLogic™ PM5000 Series Power Meters	12
3.2 Smart Demand Controller - EM7200 Series	12
3.3 EasyLogic™ PM2000 Series Power Meters	14
4. India's Most Trusted, Reliable and Accurate Multifunction Meters	
4.1 Conzerv EM6400NG Series, The Next Generation Workhorse.....	16
5. India's Most Trusted, Reliable and Accurate Multifunction Meters	
5.1 Hexa Series EM64XXH and PM1130H Meters	17
6. PowerTag - World's Smallest Energy Sensor NEW	
6.1 PowerTag for MCB	19
6.2 PowerTag for MCCB.....	19
6.3 Smartlink.....	19
6.4 Communication Auxiliaries	20
7. DIN Rail Mount Meters - Accurate, Flexible Power Meters	
7.1 PowerLogic™ PM3200 Series CI 0.5S Power Meters MV / LV Distribution	21
7.2 PowerLogic™ iEM3000 Series Class Meters - LV Distribution	21
8. Ethernet Communication Gateways and Meters	
8.1 Ethernet Communication Gateway Server / Converters.....	22
8.2 Ethernet - TCP/IP Protocol Meters & Accessories.....	22
9. Specialized Small Form Factor Meters - ELF Series	
9.1 ELF32xx Series - VAF, Power & Energy Meters.....	23
10. Specialized Counter Energy Meter - DM52xx Series	
10.1 DM52xx	23
11. LCD Display Energy Meter & VAF+PF Meter	
11.1 EM1000 / EM 1200 Series	23
11.2 DM 6100 Series - VAF, PF Meter	24
12. CE Compliance - Volt/Amp/ Frequency meter	
12.1 EasyLogic™ DM3000 / DM1000.....	24
13. Just the Basics - Voltage / Ampere / Frequency Meters	
13.1 DM3000 / DM1000.....	24



Introducing Facility Expert Energy - Our First Cloud Based EMS

Your facility at your fingertips 24x7

With EcoStruxure™ Facility Expert, you can leverage the latest cloud services and data acquisition technologies of your smart electrical distribution network to gain maximum control over your operations.

- Gain insights into energy consumption and asset status
- Improve control of energy costs
- Keep key assets up and running
- Increase maintenance efficiency


se.com/in

www.techmech.yolasite.com



Powering the Digital Future Today

Discover Our Power Monitoring Solutions






Introducing World's Most Powerful PQ Analyser

PowerLogic™ ION9000T

1. Tailored Offers for Specific Applications and Segments

Branch Circuit Power Monitor

*Price On Request



- > BCPM A/B/C variants
- > Split or solid core CTs
- > 24 / 36/ 42 / 48 / 72 / 84 channels configuration

1.1 BCPM

The BCPM Provides Data Center Managers with Information to

Maximize uptime and avoid outages through advanced alarming capabilities

- > Set sensitivity parameters so an alarm is triggered when current approaches any breaker limit
- > Alarms distinguish between past events and alarm states that are still occurring
- > Analyze the alarm history to assess areas that may need additional capacity to prevent issues

Effectively plan future infrastructure needs by providing historical usage data, to ensure that new infrastructure projects are sized correctly

- > Track usage at the circuit level
- > Develop reports on historical usage patterns
- > Use reporting to accurately predict future needs

Easily allocate costs

- > Allocate costs based on per rack energy consumption
- > Track usage patterns and determine areas of potential savings
- > Create ongoing reporting structures to effectively manage costs



1.2 Insulation Monitoring Devices

*Price On Request

Vigilohm Range of Insulation Monitoring Devices

Used in IT earthing arrangements, this solution

- > Guarantees process continuity in case of earth fault,
- > Improves staff and process safety, and
- > Optimizes maintenance.

Can be used in 3 levels of insulation monitoring


Level 1 : fault detection and signalling, manual fault location (all IMDs)

Level 2 : automatic fault location

Level 3 : feeder measurement + communication

Key features

- > Fault detection and signalling
- > Insulation resistance value display
- > Transformer monitoring (current and temperature)
- > Modbus communication
- > Alarm log
- > Insulation fault remote indicator (audible & visual)
- > Electrical fault (transformer overload or circuit breaker tripping) remote indicator (audible & visual)
- > IEC 60364-4-41 : Electrical standards in buildings
- > IEC 60364-7-10 : Requirements for special installations or locations Medical locations.
- > IEC 61557-8 : Insulation Monitoring Devices in IT earthing arrangement
- > IEC 61557-9 : Equipment for insulation fault location in IT earthing arrangements



Hospital Marine O&G Nuclear Airport MMM

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020



Discover the World's Most Accurate Advanced Power Quality Analyser

PowerLogic™ ION9000 series

Meet the future of advanced power quality metering. Modular design, multiple mounting, communication options and flexible programming gives the ION9000 the incredible adaptability needed for the IoT-enabled future. At 0.1S it exceeds even the most stringent accuracy standards, unlocking significant new energy savings for an innovative competitive edge. More than a meter; the ION9000 is the exclusive powerhouse of critical power systems.

- Highest Active Accuracy: Class 0.1S as per IEC62053-22, third party certified
- Highest Sampling Rate: 1024 Samples / Cycle
- Transient capturing as short as 20µS @50Hz
- Disturbance Direction Detection (DDD): Upstream / Downstream
- Sag/ Swell monitoring with Waveform Capturing & Smart Event Analysis
- 2GB Onboard Memory with Cyber Security compliance
- Dual Ethernet and 02 RS485 port with Modbus Mastering
- International PQ standards - IEC 61000-4-30 Class A, IEC 62586 -1/2 PQI-S

se.com/in

www.techmech.yolasite.com

2. High Accuracy, Specialized Solutions - for MV/LV Distribution



2.1 PowerLogic™ ION9000T NEW

*Price On Request

- > High-speed transient detection with 10 MHz sampling, ability to measure up to 10 kV peak
- > Patented disturbance direction detection to identify event root cause
- > Unprecedented accuracy of 0.1S accuracy
- > Certified PQI-A (power quality instrument) complies with IEC 62586-1/-2
- > Modular, flexible, and adaptable
- > Secure protocol support and security event logging.
- > Onboard power quality analysis. Complies with: IEC61000-4-30 class A, IEC62586-1 / IEC62586-2, and verified by third-party lab certifications
- > Extended waveform capture
- > High-speed RMS data capture for in-depth analysis of any PQ disturbance
- > Smart power event analysis
- > ION programmability technology allowing tremendous flexibility
- > Protects your infrastructure investment now and in the future
- > Green Premium eco-mark.
- > Makes your power network safer, more reliable, efficient, and compliant.



2.2 PowerLogic™ ION9000 NEW

*Price On Request

- > Summarize power quality, set targets, measure and verify results
- > Large Color Display with high resolution
- > Modbus Master functionality to read from downstream Modbus devices and view it via the front panel
- > Detect and capture transients as short as 20µs at 50Hz (17µs at 60 Hz)
- > Power quality compliance monitoring IEC 61000-4-30 Class A , test methods as per IEC 62586-1/2.
- > 2 GB of standard non-volatile memory.
- > Trend curves and short-term forecasting of upcoming values for better decisions
- > Disturbance direction detection with results captured in the event log, with a timestamp and certainty level
- > 50+ definable alarms to log critical event data, trigger waveform recording, or perform control function.
- > Trigger on any condition, with 1/2-cycle and 1-second response time.
- > Support protocol: Modbus, ION, DNP3, DLMS, SNMP, and IEC 61850.
- > Gateway functionality to access downstream meter's readings through ethernet
- > Time synchronization via GPS clock (RS-485) or IRIG-B (digital input) to ±1 millisecond.



Utility/ABT meter



8650

DLMS

2.3 PowerLogic™ ION 8800 / 8650

*Price On Request

- > **Utility grade accurate metering** with IEC 62053-22/23 Class 0.2S with 1024 samples / cycle
- > **Power quality compliance monitoring** for IEC 61000-4-30 Class A/S, EN50160, IEC 61000-4-7, IEC 61000-4-15, IEEE 1159, IEEE 519
- > **Power quality measurements** with Individual Harmonics, sag – swell, transient detection, waveform analysis & logging
- > **Digital fault recording** by capturing voltage and current channels simultaneously for sub-cycle disturbances
- > **Complete communications** through IEC1107 optical port or the optional communications module that supports concurrent Ethernet, serial, and modem communications
- > **Transformer/line loss compensation** for system losses in real time directly in the meter
- > **Instrument transformer correction** to save money and improve accuracy by correcting for less accurate transformers.

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

2. High Accuracy, Specialized Solutions - for MV/LV Distribution



2.4 PowerLogic™ PM8000 Series Power Quality Analyser

- > Patent disturbance detection capability with Sag/Swell / Waveform capture technology ***Price On Request**
- > **Ideal** for high energy users
- > **Revenue accuracy** of Class 0.2S as per IEC 62053-22
- > **High Sampling rate** of 256 Samples / Cycle, Waveform recording, sag/swell monitoring
- > **Modbus Master** with Single RS485 port & Dual Ethernet
- > **512MB of standard** non-volatile memory for Data and event logging
- > **Harmonics Analysis** upto 63rd for Voltage & current
- > **GPS clock (RS485)** or IRIG-B (digital input)
- > **01 Serial port** (Modbus, ION, DNP3) , Dual Ethernet port (Modbus/TCP, ION TCP, DNP3 TCP, IEC 61850)
- > **Standard Digital Input**, Expandable Digital IO, Analog IO

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020



Simplifying power quality, maximizing versatility

PowerLogic™ PM8000 series Power Quality Analyser

- Higher Sampling Rate: 256 Samples / Cycle
- Disturbance Direction Detection (DDD): Upstream / Downstream
- Sag/ Swell monitoring with Waveform Capturing functionality
- High Active Accuracy: Class 0.2S as per IEC 62053-22
- Dual Ethernet and 01 RS485 port with Modbus Mastering
- International PQ standards - IEC 61000-4-30 Class S, IEC 62586 PQI-S



se.com/in

www.techmech.yolasite.com

3. High Accuracy, Compact, Power Meters - for HV/MV/LV Distribution



3.1 PowerLogic™ PM5000 Series Power Meters

- > IEC 61557-12 IEC for PMD (Power Measurement Devices)
- > **Accuracy** - Class 0.5S (PM51xx, PM53xx) and Class 0.2S (PM5560) - IEC Specifications
- > **4th CT** for neutral and ground current measurement (PM5560)
- > **Dual Ethernet** ports for daisy chain communication (PM5560)
- > **Internal** webpage (PM5560)
- > **Individual Harmonics** up-to 63rd (PM5560), 31st (PM53xx) & 15th (PM51xx) THD, TDD
- > **Multi-tariff** Schedules 4 tariffs (PM53xx) & 8 tariffs (PM5560)
- > **Two Relay outputs** for circuit breaker monitoring & control (PM5330, PM5340)
- > **Logging** memory (PM53xx, PM5560)
- > **Peak demand** with time stamping D/T for current and powers (PM53xx, PM5560)
- > **Demand prediction** based on sliding, fixed and rolling block, thermal methods (All models)
- > **Battery backed up** Real Time Clock (All models)
- > **Meter Insight-Through QR code**

Product	Description	Reference	Unit LP [₹]
PM 5560	CI0.2S, 2 Ethernet + 1 RS485 Port, 4th CT, Webpage, 63rd Harmonic (magnitude & direction), 52 alarms, 4 DI, 2 DO, 8 multi tariff, 128 samples / cycle	30003008D	59374
PM 5340	CI0.5S, 1 Ethernet, 31st harmonic, 2 DI, 2 DO, 2 RO, 35 Alarms, Data logging, 64samples / cycle	30003007D	34729
PM 5320	CI0.5S, 1 Ethernet, 31st harmonic, 2 DI, 2 DO, 35 Alarms, Data logging, 64samples / cycle	30003005D	32369



3.2 Smart Demand Controller - EM7200 Series

- > Accuracy CL **0.2***, **0.5S** and **Class 1.0** as per IEC 62053 21/22
- > **CE / UL** Certification as per IEC / UL61010 1 Ed 3
- > Versatile and fully user programmable, suitable for HT/LT with any CT/PT
- > 2 Digital inputs, **3 Form C Relay outputs** for control
- > **TOU** for time enabled tariff users and auto resetting of energy parameters - weekdays, weekends, public holidays & offs.
- > **Import / Export** option enables monitoring of bi-directional power flow (also called 4 - quadrant measurement)
- > Utility meter cross check
- > **19 demand profile** settings for optimal demand planning
- > THD and individual harmonics up-to 15th
- > **Predictive demand**, present demand, max demand with date/time stamp. 4 peaks and 4 lows

Product	Description	Reference	Unit LP [₹]
EM 7290	Demand Controller CI0.2* with RS485 Port	30002975	48866
EM 7280	Demand Controller CI0.5S with RS485 Port	30002198	38120
EM 7230	Demand Controller CI1 with RS485 Port	30002055	35187

* Class 0.2S compliance available in 3ph,4w system

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020



The easy choice for quality,
value, and simplicity.

EasyLogic™ PM2000 series

- Active Accuracy - Class 0.5S/1.0 as per IEC62053-22/21
- Dual Sourcing - Utility or Solar or wind energy monitoring using the DI
- 12am (Configurable) Snapshot - Volt, Amp, Power & Energy
- Rate Counters - Configurable for Energy and KgCO2
- Expandable IO Module - Digital IO/Analog IO
- Calibration and Heart beat LED on the front display



NEW

se.com/in

www.techmech.yolasite.com

3. High Accuracy, Specialized Solutions- for MV/LV Distribution

3.3 Easy Logic PM2000 Series

Multifunction Power and Energy meter with 12am snapshot and Rate counters (kgCO2 / Energy)



- > Energy Standard - Class 0.5S /1.0 as per IEC 62053-22 / 21
- > Power quality analysis with THD & Ind. harmonics up to 31st
 - IO module integration (optional) – Digital Input/ Output, Analog Input/ Output
 - Dual / Multi sourcing - Capable of monitoring Utility & Genset/ Solar/Wind energy using the Multitariff and Digital Input.
 - 12am (Configurable) Snapshot – Snapshot of Avg Volt, Avg Amp, Total active power & energy delivered as measured by the meter at 12am (Configurable) of every day.
 - Rate Counters – Configurable rate counters for displaying kgCO2 or energy cost.
 - Onboard Data Logging – Configurable logging up to 2 parameters
 - Per-phase, avg/ total of Volts, Amps, PF, THD, Hz, W, Wh, VA, VAh, VAR, VARh, Max Demand & Import / Export
 - Min/Max Monitoring with Date/Time stamping
 - Communication : Pulse output or RS485 port

Product	Description	Reference	Unit LP [₹]
PM2230	PM2230, LCD, RS485, Accuracy CI0.5S, 31st Ind. harmonics, 12am snap shot, kg CO2 and energy rate counters, Data logging	METSEPM2230D	24042
PM2220	PM2220, LCD, RS485, Accuracy CI1, 15th Ind.harmonics, 12am snap shot, kg CO2 and energy rate counters	METSEPM2220D	22118
PM2210	PM2210, LCD, Pulse Output, Accuracy CI1, 12am snap shot, kg CO2 and energy rate counters	METSEPM2210D	16213
PM2130	PM2130, LED, RS485, Accuracy CI0.5S, Ind. Harmonics up to 31st over communication, data logging	METSEPM2130D	23028
PM2K2DIDO*	Optional Digital IO card - 2 channel DI & DO for PM2000 Series	METSEPM2KDGTLIO22D	2732
PM2K1AIAO*	Optional Analog IO card - 1 channel AI & AO for PM2000 Series	METSEPM2KANLGIO11D	3239
PM2K2AIAO*	Optional Analog IO card - 2 channel AI & AO for PM2000 Series	METSEPM2KANLGIO22D	3946
PM2K2DI2RO*	Easylogic PM2x30 2DI2RO Module 2-IO	METSEPM2K2DI2ROD	Price On Request

* Optional IO modules can be used for PM2230 & PM2130 models only. Maximum upto 1 module can be used per device at a time.

The future of multifunction meters is here

The all-new Hexa Series and EM6400NG Series

All-New Hexa

All-New EM6400NG



se.com/in

www.techmech.yolasite.com

4. India's Most Trusted, Reliable and Accurate Multifunction Meters



4.1 Conzerv EM6400NG Series, The Next Generation Workhorse

Multifunction Energy meter with NextGen features like Harmonics & Min/Max Monitoring, Digital security

- > **Energy Standard** – Class 0.2/0.5S/1 as per IEC 62053-22 / 21
- > **Power quality analysis** with THD & individual harmonics upto 15th over communication
- > **13 different wiring** configuration scheme
- > **Volts, Amps, PF, THD, F, W, Wh, VA, VAh, Var, Varh, Runhrs, Onhrs, Interupts,** Preloaded Demand & Import /Export
- > **Min/Max Monitoring** with Date/Time stamping
- > **Calibration LED** and Heart beat LED for communication Status
- > **Communication** : POP or RS485 port

Product	Description	Reference	Unit LP [₹]
EM6400NG	Class accuracy C10.2, RS485 port	METSEEM6400NGRSL2	26598
EM6400NG	Class accuracy C10.5S, RS485 port	METSEEM6400NGRSL5	22219
EM6400NG	Class accuracy C11.0, RS485 port	METSEEM6400NGRSL1	<input checked="" type="checkbox"/> 17538
EM6400NG	Class accuracy C10.5S, POP	METSEEM6400NGPOCL5	15193
EM6400NG	Class accuracy C11.0, POP	METSEEM6400NGPOCL1	<input checked="" type="checkbox"/> 13755

Old EM6400 Reference	Equivalent EM6400NG Reference
30002021	METSEEM6400NGPOCL1
30002065	METSEEM6400NGPOCL1
30002072	METSEEM6400NGPOCL1
30002081	METSEEM6400NGPOCL1
30002022	METSEEM6400NGPOCL5
30002034	METSEEM6400NGPOCL5
30002049	METSEEM6400NGPOCL5
30002050	METSEEM6400NGPOCL5
30002064	METSEEM6400NGPOCL5
30002085	METSEEM6400NGPOCL5
30002088	METSEEM6400NGPOCL5
30002002	METSEEM6400NGRSL1
30002012	METSEEM6400NGRSL1
30002077	METSEEM6400NGRSL1
30002078	METSEEM6400NGRSL1
30002246	METSEEM6400NGRSL1
30002027	METSEEM6400NGRSL2
30002066	METSEEM6400NGRSL2
30002089	METSEEM6400NGRSL2
30002097	METSEEM6400NGRSL2
30002101	METSEEM6400NGRSL2
30002102	METSEEM6400NGRSL2
30002104	METSEEM6400NGRSL2
30002106	METSEEM6400NGRSL2
30002109	METSEEM6400NGRSL2
30002257	METSEEM6400NGRSL2
30002347	METSEEM6400NGRSL2
30002911	METSEEM6400NGRSL2

Old EM6400 Reference	Equivalent EM6400NG Reference
30002912	METSEEM6400NGRSL2
30002913	METSEEM6400NGRSL2
30002914	METSEEM6400NGRSL2
30002915	METSEEM6400NGRSL2
30002916	METSEEM6400NGRSL2
30002917	METSEEM6400NGRSL2
30002918	METSEEM6400NGRSL2
30002919	METSEEM6400NGRSL2
30002920	METSEEM6400NGRSL2
30002921	METSEEM6400NGRSL2
30002922	METSEEM6400NGRSL2
30002923	METSEEM6400NGRSL2
30002924	METSEEM6400NGRSL2
30002925	METSEEM6400NGRSL2
30002001	METSEEM6400NGRSL5
30002019	METSEEM6400NGRSL5
30002036	METSEEM6400NGRSL5
30002040	METSEEM6400NGRSL5
30002041	METSEEM6400NGRSL5
30002042	METSEEM6400NGRSL5
30002051	METSEEM6400NGRSL5
30002056	METSEEM6400NGRSL5
30002057	METSEEM6400NGRSL5
30002069	METSEEM6400NGRSL5
30002082	METSEEM6400NGRSL5
30002083	METSEEM6400NGRSL5

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

5. India's Most Trusted, Reliable and Accurate Multifunction Meters



5.1 Hexa Series EM64XXH and PM1130H Meters

Load Managers, Power & Energy, Dual Source Multifunction meters

- > Energy Accuracy - Class 0.5 / 1.0 as per IEC 62053-22 / 21
- > Single and Multisource range of devices
- > Dual Sourcing with demand Monitoring, THD% for voltage & Current, 01 Relay Contact.
- > Configurable Favorite Page.
- > Sampling Rate of 32 Samples / Cycle.
- > Onsite Calibration Verification - Calibration LED.
- > Heart beat LED for communication status & meter healthiness.
- > Modus RS485 communication port.
- > Communication Disable from the front panel of the Meter.
- > Multi colored analog load bar with over load indication.
- > Configurable Password for secured setup of the device.

Product	Description	Reference	Unit LP [₹]
PM1130H	EASYLOGIC PM1130H Dual Source Power & Energy Meter, Class accuracy 0.5, 01 Relay Contact, 01 RS485 port	METSEPM1130HCL05RD	15378
EM6438H	CONZERV EM6438H Dual Power & Energy Meter, Class accuracy 0.5, 01 RS485 port	METSEEM6438HCL05RS	7553
EM6438H	CONZERV EM6438H Dual Power & Energy Meter, Class accuracy 1.0, 01 RS485 port	METSEEM6438HCL10RS	<input checked="" type="checkbox"/> 7012
EM6436H	CONZERV EM6436H VAF+ PF + Power & Energy Meter, Class accuracy 0.5, 01 RS485 port	METSEEM6436HCL05RS	11547
EM6436H	CONZERV EM6436H VAF+ PF + Power & Energy Meter, Class accuracy 1.0, 01 RS485 port	METSEEM6436HCL10RS	<input checked="" type="checkbox"/> 10059
EM6436H	CONZERV EM6436H VAF+ PF + Power & Energy Meter, Class accuracy 1.0	METSEEM6436HCL10NC	8606
EM6433H	CONZERV EM6433H A+ Power & Energy Meter, Class accuracy 0.5, 01 RS485 port	METSEEM6433HCL05RS	7005
EM6433H	CONZERV EM6433H A+ Power & Energy Meter, Class accuracy 1.0, 01 RS485 port	METSEEM6433HCL10RS	<input checked="" type="checkbox"/> 6599
EM6459H	CONZERV EM6459H VAF+ PF Digital Meter, Class accuracy 0.5, 01 RS485 port	METSEEM6459HCL05RS	7442
EM6459H	CONZERV EM6459H VAF+ PF Digital Meter, Class accuracy 1.0, 01 RS485 port	METSEEM6459HCL10RS	<input checked="" type="checkbox"/> 6981
EM6459H	CONZERV EM6459H VAF+ PF Digital Meter, Class accuracy 1.0	METSEEM6459HCL10NC	5453

Old EM64xx Reference	Equivalent Hexa Reference
30002277	METSEPM1130HCL05RD
30002278	METSEPM1130HCL05RD
30002306	METSEPM1130HCL05RD
30002351	METSEPM1130HCL05RD
30002438	METSEPM1130HCL05RD
30002305	METSEPM1130HCL05RD
30002437	METSEPM1130HCL05RD
30002026	METSEEM6438HCL10RS
30002269	METSEEM6438HCL05RS
30001999	METSEEM6436HCL10RS
30002892	METSEEM6436HCL10RS
30001994	METSEEM6436HCL10NC
30002295	METSEEM6436HCL10NC
30002893	METSEEM6436HCL10NC
30002015	METSEEM6436HCL05RS
30002203	METSEEM6436HCL05RS
30002204	METSEEM6436HCL05RS
30002205	METSEEM6436HCL05RS
30002201	METSEEM6436HCL05RS

Old EM64xx Reference	Equivalent Hexa Reference
30002930	METSEEM6436HCL05RS
30002931	METSEEM6436HCL05RS
30002932	METSEEM6436HCL05RS
30002933	METSEEM6436HCL05RS
30002016	METSEEM6433HCL10RS
30002031	METSEEM6433HCL10RS
30002000	METSEEM6433HCL05RS
30002336	METSEEM6433HCL05RS
30002436	METSEEM6433HCL05RS
30002926	METSEEM6433HCL05RS
30002927	METSEEM6433HCL05RS
30001804	METSEEM6459HCL10RS
30002008	METSEEM6459HCL10NC
30002220	METSEEM6459HCL05RS
30002221	METSEEM6459HCL05RS
30002224	METSEEM6459HCL05RS
30002934	METSEEM6459HCL05RS
30002935	METSEEM6459HCL05RS
30002936	METSEEM6459HCL05RS

* Few references may not be the exact equivalent, Please contact local sales representative before ordering.

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

Stay on top of it
with PowerTag



Give your business a competitive edge with PowerTag wireless energy sensors

With PowerTag™, you can add innovation to any project with one simple action. Even in panels where space is at a premium, you can easily tag circuit breakers to help your customers reduce costs and improve efficiency.

Connected by EcoStruxure™ Power – Schneider's IoT-enabled, open, and interoperable architecture – PowerTag helps you delight your customers with a solution that's small in size but large in impact.

Monitor it. Secure it.* Tag it.

* Secure it: As part of the Acti 9 communication system, PowerTag monitors loads and identifies load imbalances and overload levels before a trip occurs. PowerTag also alerts you to voltage losses, so you save time recovering your installation in the event of load downtime. An email alert means you can take preventive action thus avoiding potential downtime.



se.com/in

www.techmech.yolasite.com

6. PowerTag - World's Smallest Energy Sensor



6.1 PowerTag for MCB

Monitor Your Energy

- > Real time U, V, I, P, PF
- > Active energy metering (Class 1 EN 61557-12) partial and total
- > Load balance overview for 3P

Improve your Maintenance

- > Pre Alarm on overload
- > Specific "alarms" for U, I, P
- > Alarm on feeder voltage loss

Product	Description	Reference	Unit LP [₹]
PowerTag	PowerTag Energy M63 1P+W	A9MEM1520	7502
PowerTag	PowerTag Energy M63 1P+N Top	A9MEM1521	7502
PowerTag	PowerTag Energy M63 1P+N Bottom	A9MEM1522	7502
PowerTag	PowerTag Energy M63 3P	A9MEM1540	14999
PowerTag	PowerTag Energy M63 3P+N Top	A9MEM1541	14999
PowerTag	PowerTag Energy M63 3P+N Bottom	A9MEM1542	14999
PowerTag	PowerTag Energy F63 1P+N	A9MEM1560	8243
PowerTag	PowerTag Energy F63 3P+N	A9MEM1570	16349



6.2 PowerTag for MCCB

- > Can also be installed in existing panels, designed to enhance the monitoring of your electrical assets
- > Simplifies the connectivity of individual breakers to a Building Management System (BMS) along with ease of installation
- > Visualize in real-time on your Smartphone or PC

Product	Description	Reference	Unit LP [₹]
PowerTag	ENERGY SENSOR POWERTAG NSX - 250A 3P	LV434020	26025
PowerTag	ENERGY SENSOR POWERTAG NSX - 250A 3P+N	LV434021	28523
PowerTag	ENERGY SENSOR POWERTAG NSX - 630A 3P	LV434022	44982
PowerTag	ENERGY SENSOR POWERTAG NSX - 630A 3P+N	LV434023	49266



6.3 Smartlink

- > Compliance to IEC/EN 61131-2
- > Protection Monitoring – Device Status and alarm notifications
- > Load Control / Switching through Contactors and Impulse Relays
- > Energy Monitoring through pulse meters
- > Alarm over email and analog sensors (temperature / humidity) with Smartlink Ethernet
- > Plug & Play – Pre fabricated cables and in built web pages
- > Rated Voltage: 24V DC

Product	Description	Reference	Unit LP [₹]
Smartlink	Smartlink Modbus	A9XMSB11	36049
Smartlink	Smartlink SI-D	A9XMWD20	23198
Smartlink	Smartlink SI-B	A9XMZA08	40163

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

6. PowerTag - World's Smallest Energy Sensor (cont.)

6.4 Communication Auxiliaries

Description	Reference	Unit LP [₹]
Mounting Kit for Din Rail	A9XMFA04	1460
Prefabricated Cables M	A9XCAM06	5392
Locking Clips for Multiclip 80	A9XMLA02	445
Connectors 5 Pin	A9XC2412	7429
Prefabricated Cables L	A9XCAL06	6132
Prefabricated Cables S	A9XCAS06	5339
SEMI - Prefabricated Cables U	A9XCAU06	3686

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

7. DIN Rail Mount Meters - Accurate, Flexible Power Meters

Schneider Electric's new DIN rail mount meters are compact, versatile, high performance devices that confirm to exacting IEC standards with the added benefits of being i. Easy to install ii. Easy to modify and iii. Easy to maintain



7.1 PowerLogic™ PM3200 Series CI 0.5S Power Meters MV / LV Distribution

- > **Know network health through** all measurement parameters (I, In, U, V, PQS, E, PF, Hz, THD)
- > **Four-quadrant metering to differentiate energy**
 - Target green technologies (delivered/received)
 - Help reduce utility penalties (active/reactive)
- > **Up to 4 different time slots to manage multiple tariffs**
 - Peak, off-peak, workday, weekend
- > **DI/DO provide access to other areas of the electrical network & allow for more applications**
 - WAGES counting, remote reset, tariff control and energy pulse outputs
 - status input (circuit breaker trip or panel door opening), DO alarm for sound or light alert
- > **Data logging (PM3255)**
 - Save last 32 days, last 20 weeks and last 13 months consumption data in separate registers
 - Longer historical record helps create an accurate load profile, making benchmarking and trending easier

Product	Description	Reference	Unit LP [₹]
PM 3255	Din rail Power meter Modbus	METSEPM3255	16553
PM 3210	Din rail Power meter pulse	METSEPM3210	15085

7.2 PowerLogic™ iEM3000 Series Class Meters - LV Distribution



iEM31xx: 63A direct connect - CI1.0
iEM32xx: 1A / 5A CT connect - CI0.5S
iEM33xx: 125A direct connect - CI1.0



iEM2010

iEM3110
iEM3210
iEM3310

- > Total kWh
- > Partial kWh + date and time of last reset
- > Pulse output up to 1000pulse/kWh
- > 1 Digital Out
- > Date and time of last reset
- > MID legal metrology certification

iEM3150
iEM3250
iEM3350

- > Modbus
- > Total kWh
- > Partial kWh + date and time of last reset
- > Self powered
- > By communication: kWh, A, V, kW, PF

iEM3165, 3175
iEM3265, 3275

- > Total kWh, kVAh
- > Four quadrant
- > Partial kWh+ date and time of last reset
- > By communication: kWh, kVAh, P, Q, S, Kv, PF, 4 tariffs, digital input status, date/clock
- > 1 DI for circuit breaker status, input WAGES, 1 DO

iEM 33xx - CI1.0 , Direct current 125 A , Din Rail Meter

Product	Description	Reference	Unit LP [₹]
iEM33xx	Three Phase, 125A Direct Current, Lonwork	A9MEM3375	21707
iEM33xx	Three Phase, 125A Direct Current, BACnet	A9MEM3365	20172
iEM33xx	Three Phase, 125A Direct Current, Modbus	A9MEM3350	17164
iEM33xx	Three Phase, 125A Direct Current, PulseO/P	A9MEM3310	16194

Three phase CT Operated, Din Rail Meter / Direct Current-Three phase (upto 63A)

Product	iEM 32xx CI0.5S CT		iEM 31xx CI1.0 - Direct current	
	Reference	Unit LP [₹]	Reference	Unit LP [₹]
iEM 3x65	A9MEM3265	17486	A9MEM3165	16964
iEM 3x55	A9MEM3255	12256	A9MEM3155	13541
iEM 3x50	A9MEM3250	11492	A9MEM3150	12781
iEM 3x10	A9MEM3210	10528	A9MEM3110	11700

Please contact Customer Care Center for Stockable and Non stockable status of references.

☑ NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

8. Ethernet Communication Gateways and Meters



Com'X 510 Energy management in a box

- > Com'X 510 collects and stores consumption of WAGES (water, air, gas, electricity and steam) and environmental factors like temperature, humidity, and CO2 levels.
- > Its embedded energy management software provides immediate visibility of energy consumption that helps identify opportunities for saving energy and lowering power bills.
- > Users can analyze real-time and historical data, provide stakeholders with a comprehensive view of their energy usage.

8.1 Ethernet Communication Gateway Server / Converters

Com'X 510 Gateway Server



- > Dual Ethernet
- > Onboard storage
- > Wireless WiFi / GPRS Support
- > Cloud hosted platform
- > Local and Customized Web pages with trending and dashboard visualization
- > Modbus Gateway
- > On-Board 6 DI, 2 AI

LINK150 Protocol Converter



- > Protocol Converter from Modbus RS485 to TCP/IP
- > Two (2) Ethernet ports for daisy chain Ethernet
- > Setup through built-in web pages
- > HTTP, HTTPS, FTP, SMTP, IPV6 Support
- > 24V DC and/or POE power supply

Product	Description	Reference	Unit LP [₹]
ComX'510	Energy Gateway Server – EMS in a BOX	EBX510	47982
Link150	Protocol Converter	EGX150	29440

8.2 Ethernet – TCP/IP Protocol Meters & Accessories

Product	Description	Reference	Unit LP [₹]
ION Products	ION 8800, ION 8650, ION 9000T, ION 9000, PM8000 with Ethernet		On Request
PM 5560	Two Ethernet ports with single IP, CIO.2S, Web dashboard	30003008D	59374
PM 5340	One Ethernet port, 2 Digital Inputs, 2 Digital Outputs, 2 Relays	30003007D	34729
PM 5320	One Ethernet port, 2 Digital Inputs, 2 Digital Outputs	30003005D	32369

Accessories for Power Monitoring

Description	Reference	Unit LP [₹]
Adaptor Plate 144X144 mm	30000089	89
ELF adaptor plate	30001808	56
DM52XX Tamper protection kit - Set of 36 nos in 01 KIT	METSEDM5240TK	1043

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

9. Specialized Small Form Factor Meters - ELF Series



9.1 ELF32xx Series - VAF, Power & Energy Meters

- > Accuracy C11.0, C10.5
- > Aux Supply - 80 to 270Vac
- > Size - 96X48mm
- > Parameters - VAF, W/VA/VAr/PF
 - a) ELF3259 - VAF meter
 - b) ELF3234 - W/VA/VAr/PF
 - c) ELF3234_3 - W/VA/VAr & PF

Product	Description	Reference	Unit LP [₹]
ELF3234-3	ELF3234-3 C10.5	30000619	6572
ELF3234	ELF3234 C10.5	30000621	5625
ELF3259	ELF3259 C10.5	30000620	2823
ELF3234-3	ELF3234-3 C11.0	30000409	5250
ELF3234	ELF3234 C11.0	30000859	4498
ELF3259	ELF3259 C11.0	30000860	2252

10. Specialized Counter Energy Meters- Conzerv™ DM52xx



10.1 *Conzerv™ DM52xx

- > Accuracy C11.0, C10.5
- > Pulse output – for effective WAGES tracking on EMS systems
- > 3P4W & 3P3W wiring options

Product	Description	Unit LP [₹]
DM5240	Energy Meter 3P4W C11.0 POP <input checked="" type="checkbox"/>	4401
DM5240	Energy Meter 3P4W C10.5 POP	5220
DM5230	Energy Meter 3P3W C11.0 POP	4128
DM5230	Energy Meter 3P3W C10.5 POP	4843

*Reference code based on detailed specification, please check with local Representative

11. LCD Display Energy Meters & VAF+PF Meters



High durability, sleek LCD display energy & VAF+PF meters

11.1 EM1000 / EM1200 Series

- > Accuracy C10.5, C11.0
- > **Parameters** - KW, kWh & PF
- > **Pulse output** - for basic tracking on EMS systems
- > **RS 485** - for native integration into EMS

Product	Description	Reference	Unit LP [₹]
EM1200	EM1200 C10.5 RS	30002572	4445
EM1000	EM1000 C10.5 POP	30002571	3815
EM1200	EM1200 C11.0 RS <input checked="" type="checkbox"/>	30002565	3663
EM1000	EM1000 C11.0 POP <input checked="" type="checkbox"/>	30002568	3017

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020



11.2 DM 6100 Series – VAF, PF Meters

- > Accuracy CI0.5, CI1.0
- > **DM6100** - VAF, PF meter
- > **DM6300** - VAF, PF meter with RS 485 port

Product	Description	Reference		Unit LP [₹]
DM6300	DM6300 CI0.5 RS	30002570		3698
DM6100	DM6100 CI0.5	30002569		2918
DM6300	DM6300 CI1.0 RS	30002566		3521
DM6100	DM6100 CI1.0	30002567	<input checked="" type="checkbox"/>	2780

12. CE compliance - Volt/Amp/ frequency meter



12.1 EasyLogic™ DM3000 / DM1000

- > **CE compliance** as per latest IEC 61010-1
- > **50Hz** or 60Hz
- > **AC or DC** control power
- > **LED indicators** for phase identification in 3-ph meters
- > **Plus all features** of Conzerv range DM3000 / DM1000

Product	Description	Reference		Unit LP [₹]
DM3210	Three phase Voltmeter CI0.5	30002965		2585
DM3110	Three phase Ammeter CI0.5	30002964		2585
DM1210	Single phase Voltmeter CI0.5	30002962		1754
DM1110	Single phase Ammeter CI0.5	30002961		1754
DM1310	Frequency meter CI0.2	30002963		1335

13. Just the Basics - Voltage / Ampere / Frequency Meters



13.1 Conzerv™ DM3000 / DM1000

Accuracy

- > Volts & Amps - CI 0.5/CI1.0
- > Frequency - 0.2
- > True RMS values

Bright red LED Display

- > Full 4 Digits, 0.1% Resolution
- > 14mm height, 7 segment

User-friendly

- > Auto exit from setup
- > Elegant ergonomic design
- > Intuitive dual function key
- > Bright LED indicators - Kilo & Phase indications for measured value

Product	Description	Reference		Unit LP [₹]
DM3210	Three phase Voltmeter CI0.5	30002462	<input checked="" type="checkbox"/>	2108
DM3110	Three phase Ammeter CI0.5	30002461	<input checked="" type="checkbox"/>	2108
DM3210	Three phase Voltmeter CI1.0	30002386	<input checked="" type="checkbox"/>	1684
DM3110	Three phase Ammeter CI1.0	30002385	<input checked="" type="checkbox"/>	1684
DM1210	Single phase Voltmeter CI0.5	30002460	<input checked="" type="checkbox"/>	1427
DM1110	Single phase Ammeter CI0.5	30002459	<input checked="" type="checkbox"/>	1427
DM1210	Single phase Voltmeter CI1.0	30002366	<input checked="" type="checkbox"/>	1060
DM1110	Single phase Ammeter CI1.0	30002365	<input checked="" type="checkbox"/>	1060
DM1310	Single phase Frequency CI0.2	30002367	<input checked="" type="checkbox"/>	1060

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 27th, 2020

Introducing the world's most accurate Revenue meter with DLMS

PowerLogic™ ION8650-DLMS Next Generation Power Quality and ABT Meter



DLMS

*Price On Request



Utilities



Buildings



Industry

se.com/in

www.techmechvolasile.com

Life Is 

Schneider
 Electric

Schneider Electric India Pvt. Ltd.

Corporate Office: 9th Floor, DLF Building No. 10, Tower C, DLF Cyber City, Phase II, Gurugram 122002, Haryana
Tel.: +91 124 3940400 Fax: +91 124 4222036/ 037

Ahmedabad
Schneider Electric India (P) Ltd.
1506-1507, 15th Floor Shapth-5,
SG Highway, Ahmedabad - 380015
Tel.: 079-66826701

Cochin
Schneider Electric India (P) Ltd.
41 / 406- D1,3rd Floor, Beejay
Towers, Rajaji Road
Cochin- 682035
Tel.: 0484-3048401

Ludhiana
Schneider Electric India (P) Ltd.
Office No. - 3, 5th Floor, Novelty Plaza
Bhaiwala Chowk
Ludhiana- 140001
Tel.: 0161- 4656672-75

Secunderabad
D.No. 1-8-271, # 401, Ashoka Bhoopal
Chambers, SP Road,
Secunderabad - 500003
Tel.: 04039404000
Fax.: 040-39131313

Bengaluru
Schneider Electric India (P) Ltd.
No. 3/1, JP Techno Park,
Mezzanine Floor, Millers Tank Bund
Road, Vasanth Nagar,
Bengaluru - 560052. Tel.: 080-71481351

Coimbatore
Schneider Electric India (P) Ltd.
No. -104, Classic Tower, 3rd Floor,
Trichy Road, Coimbatore- 641018
Tel.: 0422-3940400

Mumbai
Schneider Electric India (P)(Ltd)
Marwah House, 2nd Floor
Krishanlal Marwah Marg,
Andheri (East), Mumbai - 400072
Tel.: 91-22-30263300

Vadodara
605 & 606, 6th Floor Ocean Building,
Opp.Vadodara Central, Sarabhai Road,
Vadodara-390005
Tel.: 0265-3940400

Bhubaneswar:
Schneider Electric India (P) Ltd.
6th Floor, Block A, JSS Software Technol-
ogy park , E 1/1 , Chandaka Industrial
Estate, Info City , Bhubaneswar -751025
Tel.: 0674-6672000

Jaipur
Schneider Electric India (P) Ltd.
Jaipur Business Centre 309, 3rd
Floor, Sangam Tower 190, Church
Road, Jaipur-302001
Tel.: 0141-3912903

Nagpur
Schneider Electric India (P) Ltd.
Fortune Business Centre, 6,
Basant Vihar, W.H.C Road
Shankar Nagar, Nagpur- 440010
Tel.: 0712-2558581

Vishakhapatnam
Schneider Electric India (P) Ltd.
Ratnam's Business Centre,
D.N.10-1-43, 1st Floor
Siripuram Fort,C.B.M.Compound,
Visakhapatnam- 530016
Tel.: 0891 - 2508990

Chandigarh
Schneider Electric India (P) Ltd.
2nd Floor of Tower A
Bestech Business Tower
Sector-66
Mohali- 160059
Tel.: 0172-3324500

Kolkata
Schneider Electric (I)Pvt.Ltd,
BP-4, Sector-V
Technopolis
3rd floor, Salt Lake City
Kolkata- 700 091
Tel.: 033-333640100-101

Nashik:
Schneider Electric India (P) Ltd.
401, 4th Floor Rishi Raj Towers, Jehan
Circle, Gangapur Road,
Nashik- 422013
Tel: +91-7620498557

Chennai
Schneider Electric India (P) Ltd.
No:29, 2nd floor, Bannari Amman Towers,
B-Block,RK Salai, Mylapore
Chennai - 600 004
Tel.:044- 39404000

Lucknow
Schneider Electric India (P) Ltd.
1st Floor, Asha Bhawan 27 / II -A,
Gokhale Marg, Lucknow- 226001
Tel.: 0522-4006010

Pune
Schneider Electric India (P) Ltd.
1st Floor, R.B. Business Centre
Above Dass Electronics
Sanghvi Nagar, Aundh, Pune- 411007
Tel.: 020-39404000

Customer Care Centre

Monday-Saturday, 9 a.m. to 8 p.m.

Toll-free numbers: 1800 419 4272, 1800 103 0011

Email: customer-care.in@schneider-electric.com

For more information, visit our website at: www.se.com/in

- All Prices are in Indian Rupees.
- Prices are subject to change without notice.
- Prices charged will be as prevailing on the date of dispatch.
- Maximum Retail Price (MRP) is inclusive of all taxes

- Tax incidence on invoices is basis applicable GST rates. Invoice amount not to exceed MRP.
- Invoice Amount = (MRP – less Applicable discount) + Applicable GST %

Distributor