

POLYCAB IDEAS. CONNECTED.	POLYCAB INDIA LIMITED
	PCC LP No. 05/2026-27 Dtd : 14th August 2026
List of Products Covered in Our PCC LP	
Aluminium Armoured / Unarmoured Cables	
Copper Armoured / Unarmoured Cables	
HT Cables	
1.9 KV / 3.3 KV Cables for Solar	
Instrumentation Cables	
Rubber Cables	
JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables	
RS 485 Cables	
Fire Survival Cables	
FS Aluminium Cables	

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		224	241		266
4		241	284		315
6		303	353		395
10		349	417		546
16	242	406	464		592
25	302	418	556	653	702
35	376	536	761	843	960
50	479	723	986	1124	1266
70	608	921	1323	1532	1717
95	744	1192	1702	1941	2264
120	891	1468	2083	2433	2771
150	1061	1797	2580	2837	3348
185	1288	2194	3192	3589	4217
240	1600	2776	4130	4575	5454
300	1945	3414	5107	5674	6741
400	2511	4475	6481	7200	8667
500	3045	6214	8708	10255	11500
630	3759	7643	11070	12565	15096
800	4676				
1000	5701				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		134	179		215
6		193	242		275
10		264	316		382
16	137	274	367		493
25	164	341	485	622	658
35	213	459	692	748	828
50	291	601	848	995	1092
70	396	822	1196	1375	1565
95	517	1067	1594	1820	2099
120	644	1328	1987	2306	2650
150	807	1662	2499	2789	3298
185	989	2026	3049	3488	4059
240	1257	2589	3922	4447	5195
300	1560	3203	4855	5517	6467
400	2065	4228	6395	7056	8521
500	2558	6088	8534	10050	11270
630	3212	7490	10849	12315	14794
800	4053				
1000	5063				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
Power (Al.)				
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
Power Single Core (Al.)				
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		549	761	990	1382	1640	1882
6		781	1102	1433	2053	2468	2879
10		1266	1803	2386	3158		
16	1101	1791	2679	3519	4705		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	283	398		14	1329	2196
3	360	529		16	1520	2482
4	452	682		19	1802	2916
5	575	847		24	2254	3673
6	694	993		27	2555	4186
7	723	1155		30	2848	5034
8	822	1332		37	3695	5878
10	1030	1582		44	4315	6866
12	1158	1873		61	6354	9955

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH			
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		Armoured				
2 to 4 Core	7.5%	9%	22.5%	22.5%		
5 to 10 Core	7.5%	6%	22.5%	22.5%		
12 & Above	7.5%	6%	18%	18%		

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core		3 Core	4 Core	
	2XY	2XY		2XY	2XY	
4		480		700	923	
6		707		1040	1374	
10		1199		1757	2353	
16	971	1758		2646	3487	

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	215	328	14	1225	2102
3	294	462	16	1453	2394
4	385	617	19	1726	2835
5	502	772	24	2155	3579
6	602	906	27	2416	3995
7	640	1074	30	2867	4736
8	737	1222	37	3711	5677
10	928	1497	44	4342	6767
12	1062	1793	61	6353	9316

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%	
B) Stranding (Upto 6 SQ.MM)	4%	
C) Extruded Innersheath	4%	
D OXYGEN INDEX (FR)	4%	
E) HR PVC Insulation	17.5%	
HR PVC I/S & O/S	7.5% Each	
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%	
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%	
G) PVC Insulated Cables	15%	

FRLS Loading Factor- Control Cable			LSZH		
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%	
5 - 10	7.5%	6%	22.5%	22.5%	
12 & Above	7.5%	6%	18%	18%	

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Glavanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1694	2789	4186	5079	5568	8590
35	2313	4117	6039	6915	7990	11839
50	3240	5558	8148	9593	10889	16279
70	4464	8257	11816	13795	15824	25601
95	6094		16921	19604	22356	
120	7639		20868	24866	27826	
150	9492		25683	29751	34435	
185	11674		32528	38025	43081	
240	15057		42426	49007	56327	
300	18753		54190	61971	71483	
400	24921		70082	78454	97626	
500	31030					
630	39009					
800	49401					
1000	61588					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1596	2713	4089	4974	5454	
35	2215	4027	5935	6794	7860	
50	3146	5457	8032	9463	10745	
70	4392	8128	11670	13642	15653	
95	5819		16749	19418	22160	
120	7341		20678	24645	27610	
150	9179		25488	29516	34196	
185	11312		32274	37751	42806	
240	14644					
300	18288					
400	24371					
500	30443					
630	38348					
800	48666					
1000	60811					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoion	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1809				
50		2179				
70	2372	2646				
95	2816	3158	4107	4071	5202	
120	3413	3707	4448	4539	5834	
150	4002	4337	5336	5445	6792	7350
185	4720	5086	5875	5997	7482	8066
240	6040	6468	7028	7171	8612	9118
300	6938	7348	8365	8538	9849	10840
400	8959	9361	10276	10484	11797	12402

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

EXTRA FOR SPECIAL CONSTRUCTION:

• The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 120	690
1 Core x 150	801
1 Core x 185	985
1 Core x 240	1181
1 Core x 300	1491
1 Core x 400	1799
1 Core x 500	2392
1 Core x 630	2926

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 120	1756
3 Core x 150	2152
3 Core x 185	2567
3 Core x 240	3276
3 Core x 300	3982
3 Core x 400	4960

- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	156	0.75	181	1	203	1.5	244	2.5	375
CORE	3	0.5	185	0.75	236	1	266	1.5	345	2.5	488
CORE	4	0.5	218	0.75	278	1	322	1.5	400	2.5	637
CORE	5	0.5	292	0.75	363	1	428	1.5	547	2.5	793
CORE	6	0.5	282	0.75	374	1	450	1.5	576	2.5	916
CORE	7	0.5	357	0.75	456	1	551	1.5	716	2.5	1073
CORE	8	0.5	349	0.75	473	1	568	1.5	742	2.5	1167
CORE	10	0.5	421	0.75	591	1	698	1.5	888	2.5	1424
CORE	12	0.5	474	0.75	662	1	802	1.5	1062	2.5	1759
CORE	14	0.5	600	0.75	770	1	964	1.5	1330	2.5	1995
CORE	16	0.5	638	0.75	847	1	1023	1.5	1363	2.5	2154
CORE	19	0.5	739	0.75	982	1	1245	1.5	1683	2.5	2643
CORE	24	0.5	870	0.75	1220	1	1440	1.5	1883	2.5	3335
PAIR	1	0.5	156	0.75	181	1	203	1.5	244	2.5	375
PAIR	2	0.5	237	0.75	303	1	343	1.5	425	2.5	674
PAIR	3	0.5	293	0.75	386	1	462	1.5	592	2.5	926
PAIR	4	0.5	355	0.75	483	1	581	1.5	751	2.5	1184
PAIR	5	0.5	434	0.75	599	1	708	1.5	904	2.5	1446
PAIR	6	0.5	499	0.75	689	1	833	1.5	1092	2.5	1846
PAIR	7	0.5	603	0.75	786	1	981	1.5	1345	2.5	2020
PAIR	8	0.5	639	0.75	883	1	1061	1.5	1388	2.5	2199
PAIR	10	0.5	809	0.75	1065	1	1337	1.5	1820	2.5	2790
PAIR	12	0.5	869	0.75	1235	1	1456	1.5	2002	2.5	3359
PAIR	14	0.5	1008	0.75	1397	1	1764	1.5	2459	2.5	3788
PAIR	16	0.5	1149	0.75	1538	1	1994	1.5	2749	2.5	4302
PAIR	19	0.5	1307	0.75	1821	1	2321	1.5	3212	2.5	5041
PAIR	24	0.5	1631	0.75	2345	1	3056	1.5	3908	2.5	6035
TRIAD	1	0.5	193	0.75	237	1	269	1.5	348	2.5	499
TRIAD	2	0.5	337	0.75	440	1	489	1.5	634	2.5	966
TRIAD	3	0.5	486	0.75	612	1	700	1.5	919	2.5	1358
TRIAD	4	0.5	530	0.75	723	1	835	1.5	1083	2.5	1786
TRIAD	5	0.5	678	0.75	900	1	1046	1.5	1414	2.5	2103
TRIAD	6	0.5	781	0.75	1040	1	1230	1.5	1632	2.5	2473
TRIAD	7	0.5	865	0.75	1153	1	1371	1.5	1838	2.5	2816
TRIAD	8	0.5	923	0.75	1258	1	1422	1.5	1960	2.5	3245
TRIAD	10	0.5	1152	0.75	1573	1	1866	1.5	2568	2.5	3962
TRIAD	12	0.5	1310	0.75	1806	1	2185	1.5	2999	2.5	4687
TRIAD	14	0.5	1491	0.75	2065	1	2500	1.5	3445	2.5	5396
TRIAD	16	0.5	1653	0.75	2301	1	2811	1.5	3903	2.5	6119
TRIAD	19	0.5	1906	0.75	2674	1	3272	1.5	4559	2.5	7176
TRIAD	24	0.5	2359	0.75	3346	1	4089	1.5	5740	2.5	9029
QUAD	1	0.5	226	0.75	293	1	331	1.5	435	2.5	654

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	387	0.75	435	1	425	1.5	511	2.5	828
PAIR	3	0.5	498	0.75	554	1	654	1.5	801	2.5	1130
PAIR	4	0.5	596	0.75	683	1	794	1.5	1006	2.5	1392
PAIR	5	0.5	702	0.75	807	1	958	1.5	1177	2.5	1699
PAIR	6	0.5	775	0.75	937	1	1023	1.5	1294	2.5	1978
PAIR	7	0.5	886	0.75	1036	1	1236	1.5	1561	2.5	2251
PAIR	8	0.5	1008	0.75	1146	1	1383	1.5	1770	2.5	2568
PAIR	10	0.5	1189	0.75	1399	1	1684	1.5	2164	2.5	3150
PAIR	12	0.5	1328	0.75	1628	1	1822	1.5	2385	2.5	3605
PAIR	14	0.5	1537	0.75	1830	1	2232	1.5	2884	2.5	4264
PAIR	16	0.5	1729	0.75	2059	1	2503	1.5	3251	2.5	4824
PAIR	19	0.5	1975	0.75	2369	1	2895	1.5	3797	2.5	5640
PAIR	24	0.5	2458	0.75	2977	1	3638	1.5	4788	2.5	7095
TRIAD	2	0.5	480	0.75	551	1	625	1.5	775	2.5	1070
TRIAD	3	0.5	596	0.75	702	1	815	1.5	1032	2.5	1462
TRIAD	4	0.5	728	0.75	873	1	1010	1.5	1267	2.5	1854
TRIAD	5	0.5	862	0.75	1040	1	1222	1.5	1560	2.5	2300
TRIAD	6	0.5	994	0.75	1189	1	1403	1.5	1827	2.5	2700
TRIAD	7	0.5	1100	0.75	1326	1	1574	1.5	2069	2.5	3067
TRIAD	8	0.5	1231	0.75	1524	1	1789	1.5	2359	2.5	3499
TRIAD	10	0.5	1482	0.75	1844	1	2191	1.5	2896	2.5	4349
TRIAD	12	0.5	1715	0.75	2139	1	2558	1.5	3384	2.5	5098
TRIAD	14	0.5	1927	0.75	2432	1	2938	1.5	3904	2.5	5873
TRIAD	16	0.5	2168	0.75	2742	1	3298	1.5	4416	2.5	6665
TRIAD	19	0.5	2512	0.75	3187	1	3871	1.5	5192	2.5	7807
TRIAD	24	0.5	3150	0.75	4011	1	4879	1.5	6488	2.5	9883

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						858	1262	1754	2513
2 Core	192	309	468	707	1207	1894	2886	3884	5527
3 Core	268	442	675	1018	1749	2684	4143	5717	8168
4 Core	361	581	885	1343	2295	3543	5439	7517	10808
5 Core	473	794	1216						
6 Core	537	868							
7 Core	605	989							
8 Core	695	1188							
10 Core	885	1476							
12 Core	1042	1743							
14 Core	1207	2022							
16 Core	1370	2299							
19 Core	1661	2701							
24 Core	2115	3430							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	3547	4664	5928	7386	9016	11910	14933	19640	
3 Core	11528	15160	19267	24004	29374	38532	48956	63168	
4 Core	15224	20213	25267	31585	38595	50850	63563	83697	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	168	261				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	220	338	596	1319	2517	4620

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	192	368	570			

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	206
	22 AWG	0.32	233
	20 AWG	0.50	250
	18 AWG	0.80	300
	17 AWG	1.00	333
2 Pair	24 AWG	0.205	309
	22 AWG	0.32	341
	20 AWG	0.50	356
	18 AWG	0.80	488
	17 AWG	1.00	547

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	138
	22 AWG	0.32	159
	20 AWG	0.50	176
	18 AWG	0.80	227
	17 AWG	1.00	255
2 Pair	24 AWG	0.205	214
	22 AWG	0.32	255
	20 AWG	0.50	288
	18 AWG	0.80	385
	17 AWG	1.00	441

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	231
	22 AWG	0.32	261
	20 AWG	0.50	280
	18 AWG	0.80	336
	17 AWG	1.00	373
2 Pair	24 AWG	0.205	346
	22 AWG	0.32	382
	20 AWG	0.50	399
	18 AWG	0.80	547
	17 AWG	1.00	613

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	155
	22 AWG	0.32	178
	20 AWG	0.50	197
	18 AWG	0.80	254
	17 AWG	1.00	286
2 Pair	24 AWG	0.205	240
	22 AWG	0.32	286
	20 AWG	0.50	323
	18 AWG	0.80	431
	17 AWG	1.00	494

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	375	431		544
2.5	498	677		765
4	672	876		957
6	840	1216		1440
10	1241	1836		2166
16	1746	2672		3300
25	2520	3871	4398	4839
35	3420	5281	6000	6651
50	4695	6936	7801	8970
70	6450	9973	10951	13051
95	8881	13651	14851	17551
120	13801	17266	18902	22201

Page 15 of 18

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	418	476		595
2.5	549	733		821
4	733	939		1017
6	899	1288		1515
10	1312	1918		2251
16	1821	2758		3407
25	2614	3981	4517	4962
35	3524	5407	6134	6792
50	4816	7072	7945	9136
70	6596	10153	11136	13259
95	9062	13850	15059	17787
120	14035	17490	19152	22486

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	434	499		622
2.5	568	763		855
4	757	969		1057
6	922	1327		1565
10	1341	1966		2312
16	1856	2822		3481
25	2673	4076	4630	5081
35	3593	5513	6263	6931
50	4908	7213	8108	9318
70	6717	10343	11349	13510
95	9194	14066	15307	18061
120	14241	17756	19454	22831

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables

Sq.mm.	3 Core	4 Core
16	591	755
25	816	1028
35	1004	1279
50	1251	1622
70	1670	2172
95	2058	2660
120	2481	3246
150	2985	3881
185	3645	4740
240	4606	5998
300	5588	7309
400	7025	9175